TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 10.09.2014 Revision No: 1,02

Asplit® FN Solution

00359-1171



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Asplit® FN Solution

Art.-No.

592 0060, 592 0061, 592 0062

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Mortar

1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg
Telephone +49(0)3491/635-50
Telefax +49(0)3491/635-552
Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

<u>number:</u> England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: T - Toxic, Xn - Harmful, Xi - Irritant

R phrases:

Harmful in contact with skin.

Toxic by inhalation and if swallowed.

Irritating to eyes, respiratory system and skin. Limited evidence of a carcinogenic effect.

GHS classification

Hazard categories:

Acute toxicity: Acute Tox. 3
Acute toxicity: Acute Tox. 4
Acute toxicity: Acute Tox. 3

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Carcinogenicity: Carc. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Toxic if swallowed or if inhaled. Harmful in contact with skin. Causes skin irritation.

Causes serious eye irritation. May cause respiratory irritation. Suspected of causing cancer.

2.2. Label elements

Hazardous components which must be listed on the label

2-Furaldehyde Furfuryl alcohol

Signal word: Danger

Pictograms: GHS06-GHS08

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 10.09.2014 Revision No: 1,02

Asplit® FN Solution

00359-1171







Hazard statements

H301+H331 Toxic if swallowed or if inhaled.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

2.3. Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture containing following substances with additives

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
202-627-7	2-Furaldehyde	25 - < 50 %
98-01-1	Carc. Cat. 3, T - Toxic, Xn - Harmful, Xi - Irritant R40-23/25-21-36/37/38	
605-010-00-4	Carc. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H351 H301 H331 H312 H315 H319 H335	
01-2119486861-27		
202-626-1	Furfuryl alcohol	3 - < 10 %
98-00-0	Carc. Cat. 3, T - Toxic, Xn - Harmful, Xi - Irritant R40-23-21/22-48/20-36/37	
603-018-00-2	Carc. 2, Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2, STOT SE 3, STOT RE 2; H351 H331 H302 H312 H319 H335 H373	
01-2119493965-18		

Full text of R-, H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

Seek medical treatment immediately.

After contact with skin

Wash off immediately with soap and plenty of water.

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 10.09.2014 Revision No: 1,02

Asplit® FN Solution

00359-1171



Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Consult (eye) doctor immediately.

After ingestion

Do not induce vomiting.

Summon a doctor immediately.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Harmful in contact with skin.

Toxic if swallowed or if inhaled.

Causes serious eye irritation.

Causes skin irritation.

May cause respiratory irritation.

Suspected of causing cancer.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide and carbon dioxide

Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Cool containers at risk with water spray jet.

Collect contaminated firefighting water separately, must not be discharged into the drains.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 10.09.2014 Revision No: 1,02

Asplit® FN Solution

00359-1171



7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Use only in thoroughly ventilated areas.

Provide suitable extraction at the processing machines.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Take measures against electrostatically charging.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Advice on storage compatibility

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Mortar

OFOTION 0. F

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

	CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
ſ	98-01-1	2-Furaldehyde (furfural)	2	8		TWA (8 h)	WEL
			5	20		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Pay attention to explosion protection guidelines.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off viton, minimum coat thickness 0,7 mm, permeation resistance (wear duration) approx. 30 minutes, i.e. protective glove < Vitoject 890> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (EN 368).

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 141).

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 10.09.2014 Revision No: 1,02

Asplit® FN Solution

00359-1171



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: Brown

Odour: characteristic Initial boiling point and boiling range: 100 - 200 °C

Flash point: 67 °C Lower explosion limits: n.d.

Upper explosion limits:

Density: approx. 1,21 g/cm³ Water solubility: Partially soluble

(at 20 °C)

Ignition temperature: approx. 315 °C
Viscosity / dynamic: approx. 200 mPa·s

(at 23 °C)

Viscosity / kinematic: > 7 mm²/s

(at 40 °C)

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

Avoid temperatures above 25°C .

10.5. Incompatible materials

oxidizing agents

10.6. Hazardous decomposition products

Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

Carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Toxic if swallowed or if inhaled.

Harmful in contact with skin.

No toxicological data available.

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (2-Furaldehyde), (Furfuryl alcohol)

Print date: 10.09.2014 GB - EN Page 5 of 9

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 10.09.2014

Asplit® FN Solution

00359-1171



Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (2-Furaldehyde), (Furfuryl alcohol)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Revision No: 1.02

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

Waste disposal number of waste from residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and

sealants containing organic solvents or other dangerous substances

Classified as hazardous waste.

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 2810

14.2. UN proper shipping name: TOXIC LIQUID, ORGANIC, N.O.S. (2-Furaldehyde, Furfuryl alcohol)

14.3. Transport hazard class(es):6.114.4. Packing group:IIIHazard label:6.1



Classification code:

TIP TOP Oberflaechenschutz Elbe GmbH

Revision No: 1,02 Revision date: 10.09.2014

Asplit® FN Solution

00359-1171



5 L / 30 kg Limited quantity:

Transport category: Hazard No: 60 Tunnel restriction code: F

Inland waterways transport (ADN)

UN 2810 14.1. UN number:

14.2. UN proper shipping name: TOXIC LIQUID, ORGANIC, N.O.S. (2-Furaldehyde, Furfuryl alcohol)

14.3. Transport hazard class(es): Ш 14.4. Packing group:

Hazard label: 6.1



Classification code:

Limited quantity: 5 L / 30 kg

Marine transport (IMDG)

UN 2810 14.1. UN number:

14.2. UN proper shipping name: TOXIC LIQUID, ORGANIC, N.O.S. (2-Furaldehyde, furfuryl alcohol)

14.3. Transport hazard class(es): 6.1 14.4. Packing group: Ш Hazard label: 6.1



Marine pollutant: No

Limited quantity: 5 L / 30 kgEmS: F-A, S-A

Air transport (ICAO)

14.1. UN number: **UN 2810**

TOXIC LIQUID, ORGANIC, N.O.S. (2-Furaldehyde, furfuryl alcohol, 14.2. UN proper shipping name:

solution)

14.3. Transport hazard class(es): 6.1 14.4. Packing group: Ш Hazard label: 6.1



Limited quantity Passenger: Y642 / 2 L

IATA-packing instructions - Passenger: 655 60 L IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: 663 IATA-max. quantity - Cargo: 220 I

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

Print date: 10 09 2014 GB - EN Page 7 of 9

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 10.09.2014 Revision No: 1,02

Asplit® FN Solution

00359-1171



15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

1999/13/EC (VOC): 30 %

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment

restrictions for child bearing mothers and nursing.

Additional information

Chemical prohibition regulation consider.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant R-phrases (Number and full text)

21 Harmful in contact with skin.

Harmful in contact with skin and if swallowed. 21/22

23 Toxic by inhalation.

Toxic by inhalation and if swallowed. 23/25 36/37 Irritating to eyes and respiratory system. 36/37/38 Irritating to eyes, respiratory system and skin. 40 Limited evidence of a carcinogenic effect.

48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Relevant H- and EUH-phrases (Number and full text)

H301 Toxic if swallowed.

H301+H331 Toxic if swallowed or if inhaled.

H302 Harmful if swallowed.

H312 Harmful in contact with skin. Causes skin irritation. H315

Causes serious eye irritation. H319 H331

Toxic if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 10.09.2014 Revision No: 1,02

Asplit® FN Solution

00359-1171



The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)