TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 23.07.2014 Revision No: 1,0

Asplit® HVM Hardener

00359-1222



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Asplit® HVM Hardener

Art.-No.

592 1100

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hardener

1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg
Telephone +49(0)3491/635-50
Telefax +49(0)3491/635-552
Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: C - Corrosive, Xn - Harmful

R phrases:

Harmful if swallowed.

Causes burns.

May cause sensitisation by skin contact.

GHS classification

Hazard categories:

Substance or mixture corrosive to metals: Met. Corr. 1

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1 Respiratory/skin sensitization: Skin Sens. 1

Hazard Statements:

May be corrosive to metals.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

2.2. Label elements

Hazardous components which must be listed on the label

3-Aminomethyl-3,5,5-trimethylcyclohexylamine

Xylylenediamine Salicylic acid

Signal word: Danger

Pictograms: GHS05-GHS07





Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 23.07.2014 Revision No: 1,0

Asplit® HVM Hardener

00359-1222



Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

Not known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
220-666-8	3-Aminomethyl-3,5,5-trimethylcyclohexylamine	< 15 %
2855-13-2	C - Corrosive, Xn - Harmful R21/22-34-43-52-53	
612-067-00-9	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 3; H302 H312 H314 H317 H412	
01-2119514687-32		
202-859-9	Benzyl alcohol	< 10 %
100-51-6	Xn - Harmful R20/22	
603-057-00-5	Acute Tox. 4, Acute Tox. 4; H302 H332	
01-2119492630-38		
216-032-5	Xylylenediamine	< 10 %
1477-55-0	C - Corrosive, Xn - Harmful R20/22-34-43-52-53	
	Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 3; H331 H302 H314 H317 H412 EUH071	
01-2119480150-50		
200-712-3	Salicylic acid	< 2 %
69-72-7	Xn - Harmful, Xi - Irritant R22-41	
	Acute Tox. 4, Eye Dam. 1; H302 H318	
01-2119486984-17		\neg

Full text of R-, H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

Consult a physician.

Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

In the event of symptoms refer for medical treatment.

After contact with skin

In case of contact with skin wash off immediately with plenty of water.

Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 23.07.2014 Revision No: 1,0

Asplit® HVM Hardener

00359-1222



After ingestion

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Induce vomiting only upon the advice of a physician.

Summon a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

Ammonia

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Do not use metal containers.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Avoid contact with the skin and the eyes.

Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

No special protective measures against fire required.

Revision No: 1.0

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 23.07.2014

Asplit® HVM Hardener

00359-1222



7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Do not use metal containers.

Keep at temperatures between 15°C and 20°C.

Advice on storage compatibility

Incompatible with acids.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Hardener

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

Skin protection

Long sleeved clothing (EN 368).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 141).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: pasty
Colour: Various
Odour: Amine like

pH-Value: 8,5 - 11 (30 g/l)

Initial boiling point and boiling range: > 200 °C

Flash point: 101 °C *)
Lower explosion limits: 1,3 vol. % (*)
Upper explosion limits: 13 vol. % (*)

Vapour pressure: < 5 hPa

Density (at 21 °C): 2,14 g/cm³

Density (at 21 °C):

Water solubility:

(at 20 °C)

2,14 g/cm³

Slightly miscible

Print date: 23.07.2014 GB - EN Page 4 of 8

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 23.07.2014

Asplit® HVM Hardener

00359-1222

Revision No: 1,0



Ignition temperature: 435 °C *)

thixotropic

> 250 °C Decomposition temperature: Viscosity / dynamic:

(at 20 °C)

9.2. Other information

(*) Benzyl alcohol

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with strong acids.

Gives off hydrogen by reaction with metals.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

10.5. Incompatible materials

Acids.

Hydrogen, by reaction with metals.

10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix/oral: > 2000 mg /kg ATEmix/dermal: > 2000 mg/kg ATEmix/inhalation: > 20 mg/l

Irritation and corrosivity

Causes severe skin burns and eye damage.

Sensitising effects

May cause an allergic skin reaction. (3-Aminomethyl-3,5,5-trimethylcyclohexylamine), (Xylylenediamine)

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

Print date: 23.07.2014 GB - EN Page 5 of 8

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 23.07.2014 Revision No: 1,0

Asplit® HVM Hardener

00359-1222



No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances

Classified as hazardous waste.

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.

(3-Aminomethyl-3,5,5-trimethylcyclohexylamine, Xylylenediamine)

14.3. Transport hazard class(es): 8
14.4. Packing group: III

Hazard label: 8



Classification code: C7

Limited quantity: 5 L / 30 kg

Transport category: 3
Hazard No: 80
Tunnel restriction code: E

Inland waterways transport (ADN)

<u>14.1. UN number:</u> UN2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.

(3-Aminomethyl-3,5,5-trimethylcyclohexylamine, Xylylenediamine)

14.3. Transport hazard class(es): 8

14.4. Packing group:
Hazard label: 8

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 23.07.2014

Asplit® HVM Hardener

00359-1222

Revision No: 1,0





Classification code: C7

Limited quantity: 5 L / 30 kg

Marine transport (IMDG)

14.1. UN number: UN2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.

(3-Aminomethyl-3,5,5-trimethylcyclohexylamine, Xylenediamine)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8



Marine pollutant: No

Limited quantity: 5 L / 30 kg EmS: 5 L / 30 kg

Air transport (ICAO)

14.1. UN number: UN2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.

(3-Aminomethyl-3,5,5-trimethylcyclohexylamine, Xylenediamine)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8



Limited quantity Passenger:

IATA-packing instructions - Passenger:852IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:856IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

1999/13/EC (VOC): 0 %

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment

restrictions for child bearing mothers and nursing.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

Print date: 23.07.2014 GB - EN Page 7 of 8

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 23.07.2014 Revision No: 1,0

Asplit® HVM Hardener

00359-1222



SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC = Code International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant R-phrases (Number and full text)

20/22	Harmful by inhalation and if swallowed.
21/22	Harmful in contact with skin and if swallowed.
22	Harmful if swallowed

22 Harmful if swallowed

34 Causes burns.

41 Risk of serious damage to eyes.

43 May cause sensitisation by skin contact.

Harmful to aquatic organisms.

53 May cause long-term adverse effects in the aquatic environment.

Relevant H- and EUH-phrases (Number and full text)

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects

Further Information

EUH071

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

Corrosive to the respiratory tract.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)