00359-1152



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ASPLIT VP 788 POWDER

Art.-No. 592 0070

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Filler

1.3. Details of the supplier of the safety data sheet

TIP TOP Oberflaechenschutz Elbe GmbH

Heuweg 4 D-06886 Wittenberg Telephone: Telefax:

+49(0)3491/635-50 +49(0)3491/635-552

Ingelheim)

Emergency telephone :+49 (0) 6132 / 84463 (GBK Gefahrgut Buero GmbH,

Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

This mixture is not classified as dangerous according to Directive 1999/45/EC.

GHS classification

Hazard categories: Skin corrosion/irritation: Skin Irrit. 2 Serious eye damage/eye irritation: Eye Dam. 1 Hazard Statements: Causes skin irritation. Causes serious eye damage. 2.2. Label elements

Pictograms:

GHS05



Signal word:

Danger

Hazardous components which must be listed on the label

4-Hydroxybenzenesulphonic acid

Hazard statements

H315 Causes skin irritation. H318 Causes serious eye damage.

Precautionary statements

Wear protective gloves/protective clothing/eye protection/face protection.
IF ON SKIN: Wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER or doctor/physician.

2.3. Other hazards

Dust may form explosive mixture in air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

00359-1152

Chemical characterization

Mixture of the following substances with non-hazardous admixtures

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
202-691-6	4-Hydroxybenzenesulphonic acid	< 5 %
98-67-9	C - Corrosive R34	
98-67-9	C - Corrosive R34 Met. Corr. 1, Skin Corr. 1B; H290 H314	

Full text of R and H phrases: see Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove and wash contaminated clothing before re-use.

After inhalation

Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion.

In the event of symptoms refer for medical treatment.

After contact with skin

In case of contact with skin wash off immediately with plenty of water. Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting. Call a physician immediately. Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye damage. Causes skin irritation.

Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Fire-extinguishing activities according to surrounding.

Extinguishing media which must not be used for safety reasons

Full water jet.

5.2. Special hazards arising from the substance or mixture

Dust may form explosive mixture in air. Fire may produce: Carbon monoxide, carbon dioxide and sulphur oxides.

5.3. Advice for firefighters

In case of fire, wear suitable respiratory equipment with positive air supply. Protective suit.

Additional information

Cool containers at risk with water spray jet. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures



00359-1152

6.1. Personal precautions, protective equipment and emergency procedures

Avoid the formation and deposition of dust.

In case of respirable dust, use a self-contained breathing apparatus. Ensure adequate ventilation.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Pick up mechanically, avoiding dust, and provide disposal in suitable recipients.

Where possible recycling is preferred to disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal look up chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Avoid the formation and deposition of dust.

Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

Advice on protection against fire and explosion

Dust may form explosive mixture in air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Advice on storage compatibility

No materials to be especially mentioned.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Filler

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
7440-44-0	Graphite, respirable	-	4		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

Additional advice on limit values

Obey TLV for common dust, if applicable.

8.2. Exposure controls

Occupational exposure controls

Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

Protective and hygiene measures

Do not breathe dust.

Wash hands before breaks and at the end of workday.

When using, do not eat, drink or smoke.

Remove and wash contaminated clothing before re-use.

Respiratory protection

Dust mask (EN 149)

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm,





Test method

ASPLIT VP 788 POWDER

00359-1152

permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

Eye protection

Safety goggles with side protection. Eye wash bottle with pure water.

Skin protection

Long sleeved clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Powder
Colour:	Black
Odour:	Odourless

Changes in the physical state

Flash point:	n.a.
Lower explosion limits:	n.a.
Upper explosion limits:	
Ignition temperature:	n.a.
Density (at 20 °C):	~ 0,8 g/cm³
Water solubility: (at 20 °C)	More or less insoluble

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No hazardous reactions known.

10.4. Conditions to avoid

Avoid the formation and deposition of dust. Dust may form explosive mixture in air.

10.5. Incompatible materials

No materials to be especially mentioned.

10.6. Hazardous decomposition products

No hazardous decomposition products known. Fire may produce: Carbon monoxide, carbon dioxide, sulphur oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

No toxicological data available.

Irritation and corrosivity

Eye irritation: Causes serious eye damage. Skin irritation: Irritant **Sensitising effects** Not classified.

00359-1152

Severe effects after repeated or prolonged exposure

STOT - Single exposure: Not classified.

STOT - Repeated exposure: Not classified.

Aspiration hazard: Not classified.

Carcinogenic/mutagenic/toxic effects for reproduction

Carcinogenicity: Not classified.

Mutagenicity: Not classified.

Teratogenicity: Not classified.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Empirical data on effects on humans

Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Low hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.

Where possible recycling is preferred to disposal.

Waste disposal number of waste from residues/unused products

080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Other applicable information

No hazardous material as defined by the transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture				
EU regulatory information				
1999/13/EC (VOC):	0 %			
National regulatory information				
Employment restrictions:	Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing.			

REMA NDD

ASPLIT VP 788 POWDER

00359-1152

Water contaminating class (D):

1 - slightly water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Full text of R phrases referred to under Sections 2 and 3

34 Causes burns.

Full text of H statements referred to under Sections 2 and 3

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)