

ASPLIT VEQ POWDER

00359-1203

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ASPLIT VEQ POWDER

Art.-No.

592 0360

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Filler

1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflächenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50

Telefax: +49(0)3491/635-552

Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number:

England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24
24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: Xn - Harmful

R phrases:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

GHS classification

Hazard categories:

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazard Statements:

May cause damage to organs (lung) through prolonged or repeated exposure if inhaled.

2.2. Label elements

Hazardous components which must be listed on the label

Quartz

Signal word: Warning

Pictograms: GHS08



Hazard statements

H373 May cause damage to organs (lung) through prolonged or repeated exposure if inhaled.

Precautionary statements

P260 Do not breathe dust.

P285 In case of inadequate ventilation wear respiratory protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

Special labelling of certain mixtures

EUH208 Contains Dibenzoyl peroxide. May produce an allergic reaction.

2.3. Other hazards

Not known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of the following substances with non-hazardous admixtures

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
238-878-4	Quartz	> 90 %
14808-60-7	Xn - Harmful R48/20	
	STOT RE 2; H373	
202-327-6	Dibenzoyl peroxide	< 1 %
94-36-0	E - Explosive, O - Oxidizing, Xi - Irritant R3-7-36-43	
617-008-00-0	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1; H241 H319 H317 H400	
01-2119511472-50		

Full text of R and H phrases: see Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove and wash contaminated clothing before re-use.

After inhalation

Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion.

In the event of symptoms refer for medical treatment.

After contact with skin

No specific precautions required.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

If eye irritation persists, consult a specialist.

After ingestion

In the event of symptoms refer for medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

May cause damage to organs through prolonged or repeated exposure. [lung]

When dust is produced, slight irritations of eyes and mucous membranes are possible.

Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough.

May cause sensitization of susceptible persons by skin contact.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Product does not burn, fire-extinguishing activities according to surrounding.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

No data available.

5.3. Advice for firefighters

In case of fire, wear suitable respiratory equipment with positive air supply.

Protective suit.

ASPLIT VEQ POWDER

00359-1203

Additional information

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of respirable dust, use a self-contained breathing apparatus.

Ensure adequate ventilation.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Pick up mechanically, avoiding dust, and provide disposal in suitable recipients.

Where possible recycling is preferred to disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Avoid the formation and deposition of dust.

Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

Advice on protection against fire and explosion

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Advice on storage compatibility

No materials to be especially mentioned.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Filler

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
94-36-0	Dibenzoyl peroxide	-	5		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

Additional advice on limit values

Obey TLV for common dust, if applicable.

8.2. Exposure controls

Appropriate engineering controls

Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

Protective and hygiene measures

Do not breathe dust.

Wash hands before breaks and at the end of workday.

ASPLIT VEQ POWDER

00359-1203

When using, do not eat, drink or smoke.

Remove and wash contaminated clothing before re-use.

Eye/face protection

Safety goggles with side protection (EN 166).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

Skin protection

Long sleeved clothing (EN 368).

Respiratory protection

Dust mask (EN 149)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Powder
Colour:	Grey
Odour:	Odourless
Flash point:	n.a.
Lower explosion limits:	n.a.
Upper explosion limits:	
Bulk density:	1370 kg/m ³
Water solubility: (at 20 °C)	More or less insoluble
Ignition temperature:	n.a.

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No hazardous reactions known.

10.4. Conditions to avoid

Not known.

10.5. Incompatible materials

No materials to be especially mentioned.

10.6. Hazardous decomposition products

No data available.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

No toxicological data available.

ASPLIT VEQ POWDER

00359-1203

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

May cause damage to organs (lung) through prolonged or repeated exposure if inhaled. (Quartz)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

When dust is produced, slight irritations of eyes and mucous membranes are possible.

Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough.

May cause sensitization of susceptible persons by skin contact.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

No data available.

Further information

Ecological injuries are not known or expected under normal use.

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.

Where possible recycling is preferred to disposal.

Waste disposal number of waste from residues/unused products

080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID); Marine transport (IMDG); Air transport (ICAO); Inland waterways transport (ADN)

14.1. UN number:

No hazardous material as defined by the transport regulations.

14.2. UN proper shipping name:

No hazardous material as defined by the transport regulations.

14.3. Transport hazard class(es):

No hazardous material as defined by the transport regulations.

14.4. Packing group:

No hazardous material as defined by the transport regulations.

14.5. Environmental hazards

No hazardous material as defined by the transport regulations.

14.6. Special precautions for user

No hazardous material as defined by the transport regulations.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No hazardous material as defined by the transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

1999/13/EC (VOC): 0 %

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC = Code International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Full text of R phrases referred to under Sections 2 and 3

03 Extreme risk of explosion by shock, friction, fire or other sources of ignition.

07 May cause fire.

36 Irritating to eyes.

43 May cause sensitisation by skin contact.

48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.



ASPLIT VEQ POWDER

00359-1203

Full text of H statements referred to under Sections 2 and 3

H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H373	May cause damage to organs (lung) through prolonged or repeated exposure if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)