TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 17.07.2013 Revision No: 1,00



00359-1155



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP CHEMOKITT UP HARDENER 1

Art.-No. 591 0105

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hardener

1.3. Details of the supplier of the safety data sheet

TIP TOP Oberflaechenschutz Elbe GmbH

Heuweg 4

D-06886 Wittenberg

Telephone: +49(0)3491/635-50Telefax: +49(0)3491/635-552Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone

Emergency telephone: +49 (0) 6132 / 84463 (GBK GmbH, Ingelheim)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: O - Oxidizing, Xi - Irritant

R phrases: May cause fire. Irritating to eyes.

May cause sensitisation by skin contact.

May cause long-term adverse effects in the aquatic environment.

GHS classification

Hazard categories:

Organic peroxide: Org. Perox. E

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory/skin sensitization: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Acute 1 Hazardous to the aquatic environment: Aquatic Chronic 4

Hazard Statements:
Heating may cause a fire.
Causes serious eye irritation.
May cause an allergic skin reaction.

Very toxic to aquatic life.

May cause long lasting harmful effects to aquatic life.

2.2. Label elements

Pictograms:

GHS02-GHS07-GHS09







Signal word:

Danger

Hazardous components which must be listed on the label

Dibenzoyl peroxide

Hazard statements

H242 Heating may cause a fire.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

Print date: 17.07.2013 GB - EN Page 1 of 8

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 17.07.2013 Revision No: 1,00



TIP TOP CHEMOKITT UP HARDENER 1

00359-1155

H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P220 Keep/Store away from Soil, rust, chemicals, strong acids and bases and accelerators (heavy metal

salts, amines).

P234 Keep only in original container.
P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eve protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P411+P235 Store at temperatures not exceeding + 30 °C/... °F. Keep cool.

2.3. Other hazards

Not known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Hardener based on dibenzoyl peroxide

Hazardous components

EC No	Chemical name	Quantity	
CAS No	Classification		
Index No	GHS classification		
REACH No			
226-641-8	2-Ethylhexyl benzoate	40 - 50 %	
5444-75-7	R53		
	Aquatic Chronic 4; H413		
202-327-6	Dibenzoyl peroxide	30 - 40 %	
94-36-0	E - Explosive, O - Oxidizing, Xi - Irritant R3-7-36-43		
617-008-00-0	-00-0 Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1; H241 H319 H317 H400		
01-2119511472-50			
	Poly ethylene/propylene glycol monoether	2,5 - 5 %	
9038-95-3	Xn - Harmful R22		
	Acute Tox. 4; H302		

Full text of R and H phrases: see Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

Adhere to personal protective measures when giving first aid.

Symptoms of poisoning may not appear for several hours. Keep under medical supervision for at least 48 hours.

After inhalation

Supply fresh air, if required oxygen, consult a physician.

If patient is not breathing, apply artificial respiration.

Remove the casualty into fresh air and keep him immobile.

In case of the person being unconscious put him/her in a stable side position.

After contact with skin

Wash off immediately with soap and plenty of water.

Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

After ingestion

Summon a doctor immediately.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 17.07.2013 Revision No: 1,00





TIP TOP CHEMOKITT UP HARDENER 1

00359-1155

Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eve irritation.

May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Extinguishing media which must not be used for safety reasons

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide and carbon dioxide.

Hydrocarbons.

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

Additional information

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Shovel into suitable container for disposal.

Soak up with inert absorbent material (e.g. vermiculite, clean sand).

In compliance with regulations by local authorities this can be subjected to a special treatment (e.g. thermal utilization)

after dilution with an inert solid to 10% content of peroxides.

Do not keep container sealed.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Wash hands before breaks and at the end of workday.

Keep away from acids, bases, heavy metal salts and reducing agents.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Keep away from open flames, hot surfaces and sources of ignition.

Use explosion-proof equipment / fittings and non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in original container.

Keep container tightly closed in a dry, cool and well-ventilated place.

Protect against direct sun radiation.

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 17.07.2013 Revision No: 1,00



00359-1155

Recommended storage temperature: +5°C - +25°C

Advice on storage compatibility

Incompatible with:

Reducing agents., Heavy metal salts, Acids and bases.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Hardener

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
94-36-0	Dibenzoyl peroxide	-	5		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

8.2. Exposure controls

Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Remove and wash contaminated clothing before re-use.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

Eye protection

Tightly fitting goggles.

Eye wash bottle with pure water.

Skin protection

Long sleeved clothing.

Apron.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Suspension
Colour: White
Odour: characteristic

Test method

Changes in the physical state

Flash point: n.d.

Explosive properties

The product is considered non-explosive; nevertheless explosive dust/air mixture can be generated

Lower explosion limits: Upper explosion limits:

n.d.

Print date: 17.07.2013 GB - EN Page 4 of 8

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 17.07.2013 Revision No: 1,00



TIP TOP CHEMOKITT UP HARDENER 1

00359-1155

Ignition temperature:

1,1 g/cm³

Density (at 20 °C): Water solubility:

Slightly miscible

n.d.

(at 20 °C)

9.2. Other information

SADT > 60°C

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored normally.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts with:

Soil, rust, chemicals, strong acids and bases and accelerators (heavy metal salts, amines).

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Self-Accelerating decomposition temperature (SADT) from 60°C (SADT).

10.5. Incompatible materials

Soil, rust, chemicals, strong acids and bases and accelerators (heavy metal salts, amines).

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Hydrocarbons

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

No toxicological data available.

Dibenzoyl peroxide

LD50/oral/rat: > 5000 mg/kg

2-Ethylhexyl benzoate

LD50/oral/rat: > 2000 mg/kg

Irritation and corrosivity

Eye irritation: Irritant

Skin irritation: Not classified.

Sensitising effects

May cause an allergic skin reaction.

Severe effects after repeated or prolonged exposure

STOT - Single exposure: Not classified.

STOT - Repeated exposure: Not classified.

Aspiration hazard: Not classified.

Carcinogenic/mutagenic/toxic effects for reproduction

Carcinogenicity: Not classified. Mutagenicity: Not classified. Teratogenicity: Not classified.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Very toxic to aquatic organisms.

May cause long lasting harmful effects to aquatic life.

Dibenzoyl peroxide

LC50/Oncorhynchus mykiss/96 h = 0,0602 mg/l

EC50/Daphnia magna/48 h = 0,110 mg/l

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 17.07.2013 Revision No: 1,00



00359-1155

EC50/Pseudokirchneriela subcapitata/72 h = 0,0711 mg/l

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Low hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

Risk of drinking water contamination even when low quantities are released into the ground.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

In compliance with regulations by local authorities this can be subjected to a special treatment (e.g. thermal utilization) after dilution with an inert solid to 10% content of peroxides.

Where possible recycling is preferred to disposal.

Waste disposal number of waste from residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances

Classified as hazardous waste.

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed of like the product.

i ackaging that carmot be cleaned should be disposed of like the produ

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN3107

14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE E, LIQUID (Dibenzoyl peroxide)

14.3. Transport hazard class(es):5.2Hazard label:5.2



Classification code:

Limited quantity: 125 mL / 30 kg

Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN3107

14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE E, LIQUID (Dibenzoyl peroxide)

14.3. Transport hazard class(es): 5.2 Hazard label: 5.2



Classification code: P1

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 17.07.2013 Revision No: 1,00



00359-1155

Limited quantity: 125 mL / 30 kg

Marine transport (IMDG)

14.1. UN number: UN3107

14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE E, LIQUID (Dibenzoyl peroxide)

14.3. Transport hazard class(es): 5.2 Hazard label: 5.2



Limited quantity: 125 mL / 30 kg EmS: F-J, S-R

Air transport (ICAO)

UN/ID number: UN3107

14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE E, LIQUID (Dibenzoyl peroxide)

14.3. Transport hazard class(es):5.2Hazard label:5.2



Limited quantity Passenger: Forbidden IATA-packing instructions - Passenger: 570

IATA-max. quantity - Passenger:

IATA-packing instructions - Cargo:

IATA-max. quantity - Cargo:

25 L

14.5. Environmental hazards

Dangerous for the environment: yes



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

1999/13/EC (VOC): 0 %

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment

restrictions for child bearing mothers and nursing.

Water contaminating class (D): 1 - slightly water contaminating

Additional information

Chemical prohibition regulation consider.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Full text of R phrases referred to under Sections 2 and 3

O3 Extreme risk of explosion by shock, friction, fire or other sources of ignition.

07 May cause fire.

Harmful if swallowed.

36 Irritating to eyes.

43 May cause sensitisation by skin contact.

Print date: 17.07.2013 GB - EN Page 7 of 8



TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 17.07.2013 Revision No: 1,00



TIP TOP CHEMOKITT UP HARDENER 1

00359-1155

53 May cause long-term adverse effects in the aquatic environment.

Full text of H statements referred to under Sections 2 and 3

H241	Heating may cause a fire or explosion.
H242	Heating may cause a fire.
H302	Harmful if swallowed.
11047	Manager and all and a little and attack

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H400 Very toxic to aquatic life.

H413 May cause long lasting harmful effects to aquatic life.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)