

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP COROFLAKE 200 B

Art.-No.

590 0796, 590 0797, 590 1393, 590 1394

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hardener

1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflächenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone +49(0)3491/635-50

Telefax +49(0)3491/635-552

Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone

number: INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24
24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: C - Corrosive, Xn - Harmful

R phrases:

Harmful by inhalation, in contact with skin and if swallowed.

Causes burns.

May cause sensitisation by skin contact.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

GHS classification

Hazard categories:

Skin corrosion/irritation: Skin Corr. 1A

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory/skin sensitization: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazardous components which must be listed on the label

Triethylenetetramine

2-Propenenitril Polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl- terminated

Cyclohex-1,2-ylenediamine

2-Piperazin-1-ylethylamine

Signal word:

Danger

Pictograms:

GHS05-GHS07



Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

TIP TOP COROFLAKE 200 B

00359-1019

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P273 Avoid release to the environment.

2.3. Other hazards

Not known.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Hardener based on aliphatic polyamines

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
203-950-6	Triethylenetetramine	< 45 %
112-24-3	C - Corrosive, Xn - Harmful R21-34-43-52-53	
612-059-00-5	Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 3; H312 H314 H317 H412	
	2-Propenenitril Polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl- terminated	< 30 %
68683-29-4	R43	
	Skin Sens. 1; H317	
202-859-9	Benzyl alcohol	< 15 %
100-51-6	Xn - Harmful R20/22	
603-057-00-5	Acute Tox. 4, Acute Tox. 4; H302 H332	
01-2119492630-38		
211-776-7	Cyclohex-1,2-ylenediamine	< 10 %
694-83-7	C - Corrosive, Xn - Harmful, Xi - Irritant R20/21/22-35-37	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A, STOT SE 3; H302 H312 H332 H314 H335	
01-2119976312-37		
205-411-0	2-Piperazin-1-ylethylamine	< 5 %
140-31-8	C - Corrosive, Xn - Harmful R21/22-34-43-52-53	
612-105-00-4	Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 3; H311 H302 H314 H317 H412	
01-2119471486-30		
203-986-2	Tetraethylenepentamine	< 1 %
112-57-2	C - Corrosive, Xn - Harmful, N - Dangerous for the environment R21/22-34-43-51-53	
612-060-00-0	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 2; H312 H302 H314 H317 H411	
203-865-4	Diethylenetriamine	< 1 %
111-40-0	C - Corrosive, Xn - Harmful R21/22-34-43	
612-058-00-X	Acute Tox. 2, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1; H330 H302 H312 H314 H317	
01-2119473793-27		

Full text of R-, H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
Call a physician immediately.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
In the event of symptoms refer for medical treatment.

After contact with skin

In case of contact with skin wash off immediately with plenty of water.
Seek medical treatment immediately.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Consult (eye) doctor immediately.

After ingestion

Induce vomiting only upon the advice of a physician.
Drink plenty of water or milk.
Never give anything by mouth to an unconscious person.
Do not induce vomiting.
Summon a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:
Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x).

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.
Protective suit.

Additional information

Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.
Ensure adequate ventilation.
Use personal protective clothing.

6.2. Environmental precautions

Clean contaminated surface thoroughly.
Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.
Do not breathe vapours.
Use only in thoroughly ventilated areas.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Advice on storage compatibility

Incompatible with:
Acids and oxidizing agents.
Halogenated compounds.
Acrylates, aldehydes, ketones, copper and copper alloys.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Hardener

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
111-40-0	2,2'-Iminodi(ethylamine)	1	4.3		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Wash hands before breaks and immediately after handling the product.
When using do not eat, drink or smoke.
Remove and wash contaminated clothes before re-use.
Avoid contact with eyes, skin or mucous membrane.

Eye/face protection

Tightly fitting goggles (EN 166).
Eye wash bottle with pure water (EN 15154).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

Skin protection

Long sleeved clothing (EN 368).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 141).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	Yellowish	
Odour:	Amine like	
Flash point:	> 100 °C	
Lower explosion limits:	n.d.	
Density (at 20 °C):	0,98 - 1,04 g/cm³	
Water solubility: (at 20 °C)	Immiscible	
Ignition temperature:	n.d.	
Viscosity / dynamic: (at 25 °C)	400 - 600 mPa·s	
Flow time: (at 25 °C)	< 40 s	6 DIN/ISO 2431

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids and strong oxidizing agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

10.5. Incompatible materials

Acids and oxidizing agents.

Halogenated compounds.

Acrylates, aldehydes, ketones, copper and copper alloys.

10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

No toxicological data available.

ATEmix/oral: > 2000 mg/kg

ATEmix/dermal: > 2000 mg/kg

ATEmix/inhalation: > 20 mg/l/4h

Irritation and corrosivity

Causes severe skin burns and eye damage.

Sensitising effects

May cause an allergic skin reaction. (Triethylenetetramine), (2-Propenenitril Polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl- terminated), (2-Piperazin-1-ylethylamine), (Tetraethylenepentamine), (Diethylenetriamine)

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances
Classified as hazardous waste.

Contaminated packaging

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

UN3267

14.2. UN proper shipping name:

CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Triethylenetetramine, 1,2-Cyclohexanediamine)

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

Hazard label:

8



Classification code:

C7

Limited quantity:

1 L / 30 kg

Transport category:

2

Hazard No:

80

Tunnel restriction code:

E

Inland waterways transport (ADN)

14.1. UN number:

UN3267

14.2. UN proper shipping name:

CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Triethylenetetramine, 1,2-Cyclohexanediamine)

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

Hazard label:

8



Classification code:

C7

Limited quantity:

1 L / 30 kg

Marine transport (IMDG)

14.1. UN number:

UN3267

14.2. UN proper shipping name:

CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (triethylene tetramine and 1,2-cyclohexane diamine)

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

Hazard label:

8



Marine pollutant:

No

Limited quantity:

1 L / 30 kg

EmS:

F-A, S-B

Air transport (ICAO)

14.1. UN number:

UN3267

14.2. UN proper shipping name:

CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (triethylene tetramine and 1,2-cyclohexane diamine)

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

Hazard label:

8



Limited quantity Passenger:

Y840 / 0.5 L

IATA-packing instructions - Passenger:

851

IATA-max. quantity - Passenger:

1 L

IATA-packing instructions - Cargo:

855

IATA-max. quantity - Cargo:

30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

1999/13/EC (VOC): 0 %

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant R-phrases (Number and full text)

20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

20/22 Harmful by inhalation and if swallowed.

21 Harmful in contact with skin.

21/22 Harmful in contact with skin and if swallowed.

34 Causes burns.

35 Causes severe burns.

37 Irritating to respiratory system.

43 May cause sensitisation by skin contact.

51 Toxic to aquatic organisms.

52 Harmful to aquatic organisms.

53 May cause long-term adverse effects in the aquatic environment.

Relevant H- and EUH-phrases (Number and full text)

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.



TIP TOP COROFLAKE 200 B

00359-1019

H317	May cause an allergic skin reaction.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)