TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 17.07.2013 Revision No: 1,01



00359-1036



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

TIP TOP COROFLAKE 60 B

**Art.-No.** 590 0916

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Hardener

### 1.3. Details of the supplier of the safety data sheet

TIP TOP Oberflaechenschutz Elbe GmbH

Heuweg 4

D-06886 Wittenberg

Telephone: +49(0)3491/635-50Telefax: +49(0)3491/635-552Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone

Emergency telephone: +49 (0) 6132 / 84463 (GBK GmbH, Ingelheim)

number:

## **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Indications of danger: T - Toxic, C - Corrosive, Xn - Harmful

R phrases:

May cause harm to the unborn child.

Harmful if swallowed.

Causes burns.

May cause sensitisation by skin contact.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

# **GHS** classification

Hazard categories:

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1 Respiratory/skin sensitization: Skin Sens. 1

Reproductive toxicity: Repr. 1B

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May damage the unborn child.

Harmful to aquatic life with long lasting effects.

# 2.2. Label elements

## Pictograms:





Signal word:

Danger

## Hazardous components which must be listed on the label

3-aminomethyl-3,5,5-trimethylcyclohexylamine

2.2.4(or 2.4.4)-trimethylhexane-1.6-diamine

Epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)

1,3-Diaza-2,4-cyclopentadiene

## **Hazard statements**

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

Print date: 17.07.2013 GB - EN Page 1 of 8

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 17.07.2013 Revision No: 1,01



00359-1036

H360D May damage the unborn child.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P273 Avoid release to the environment.

P405 Store locked up.

Special labelling of certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Restricted to professional users.

2.3. Other hazards

No data available.

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

#### **Chemical characterization**

Preparation contains epoxy resins and polyamines

## **Hazardous components**

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
202-859-9	benzyl alcohol	< 15 %
100-51-6	Xn - Harmful R20/22	
603-057-00-5	Acute Tox. 4, Acute Tox. 4; H302 H332	
01-2119492630-38		
220-666-8	3-aminomethyl-3,5,5-trimethylcyclohexylamine	< 10 %
2855-13-2	C - Corrosive, Xn - Harmful R21/22-34-43-52-53	
612-067-00-9	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 3; H302 H312 H314 H317 H412	
01-2119514687-32		
247-063-2	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	< 10 %
25513-64-8	C - Corrosive, Xn - Harmful R22-34-43-52-53	
	Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 3; H302 H314 H317 H412	
01-2119569598-25		
500-033-5	-033-5 Epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	
25068-38-6	Xi - Irritant, N - Dangerous for the environment R36/38-43-51-53	
603-074-00-8	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411	
01-2119456619-26		
206-019-2	1,3-Diaza-2,4-cyclopentadiene	< 1 %
288-32-4	Repr. Cat. 2, C - Corrosive, Xn - Harmful R61-22-34	
	Acute Tox. 4, Skin Corr. 1C, Repr. 1B; H302 H314 H360D	
01-2119485825-24		

Full text of R and H phrases: see Section 16.

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

# **General information**

Remove contaminated soaked clothing immediately.

Print date: 17.07.2013 GB - EN Page 2 of 8



TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 17.07.2013 Revision No: 1,01



00359-1036

Call a physician immediately.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours.

In the event of symptoms refer for medical treatment.

#### After contact with skin

In case of contact with skin wash off immediately with plenty of water.

Seek medical treatment immediately.

### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Summon a doctor immediately.

## After ingestion

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

## 4.2. Most important symptoms and effects, both acute and delayed

May cause harm to the unborn child.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Attention. Beware, danger of aspiration.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

### Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

#### Extinguishing media which must not be used for safety reasons

Full water jet.

#### 5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

#### 5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

#### Additional information

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

# 6.2. Environmental precautions

Clean contaminated surface thoroughly.

Do not discharge into the drains/surface waters/ground water.

### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

## 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

## **SECTION 7: Handling and storage**

Print date: 17.07.2013 GB - EN Page 3 of 8



TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 17.07.2013 Revision No: 1,01



00359-1036



#### Advice on safe handling

Keep container tightly closed.

Handle and open container with care.

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

### Advice on protection against fire and explosion

No special protective measures against fire required.

# 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

#### Advice on storage compatibility

Incompatible with:

Oxidizing agents

Amines

Acids and bases.

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

#### 7.3. Specific end use(s)

Hardener

\_\_\_\_\_\_

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

#### **Exposure limits (EH40)**

	CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
Ī	12001-26-2	Mica, respirable	-	0.8		TWA (8 h)	WEL
			-	-		STEL (15 min)	WEL

#### 8.2. Exposure controls

# Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

### Protective and hygiene measures

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

#### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

## Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

#### Eye protection

Tightly fitting goggles.

Eye wash bottle with pure water.

## Skin protection

Long sleeved clothing.





TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 17.07.2013 Revision No: 1,01



00359-1036



#### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Yellowish
Odour: Mild

Test method

Changes in the physical state

Flash point: > 100 °C

Lower explosion limits: n.d.

Ignition temperature: n.d.

Density (at 20 °C): 1,25 g/cm³

Water solubility: Immiscible

Viscosity / dynamic: 1100 - 1500 mPa·s

(at 25 °C)

Flow time: > 40 s 6 DIN/ISO 2431

(at 25 °C)

# 9.2. Other information

No data available.

\_\_\_\_\_

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No data available.

# 10.2. Chemical stability

Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents

Reactions with amines.

### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

## 10.5. Incompatible materials

oxidizing agents

Acids and bases.

Amines

### 10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

Ammonia

## **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

## **Acute toxicity**

No toxicological data available. ATEmix/oral: > 2000 mg/kg ATEmix/dermal: > 2000 mg/kg

## Irritation and corrosivity

Causes severe skin burns and eye damage.

### Sensitising effects

May cause an allergic skin reaction.

# Severe effects after repeated or prolonged exposure

STOT - Single exposure: Not classified. STOT - Repeated exposure: Not classified.

Aspiration hazard: Not classified.

## Carcinogenic/mutagenic/toxic effects for reproduction

Carcinogenicity: Not classified.

Print date: 17.07.2013 GB - EN Page 5 of 8

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 17.07.2013 Revision No: 1,01



00359-1036

Mutagenicity: Not classified.

Teratogenicity: Category 1B [May cause harm to the unborn child.]

### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

## **SECTION 12: Ecological information**

# 12.1. Toxicity

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

LC50/Oncorhynchus mykiss/96 h = 2 mg/l

EC50/Daphnia magna/48 h = 1,8 mg/l

ErC50/Scenedesmus capricornutum/72 h = 11 mg/l

### 12.2. Persistence and degradability

Not readily biodegradable.

### 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

#### 12.6. Other adverse effects

Hazardous water pollutant.

#### **Further information**

Do not flush into surface water or sanitary sewer system.

## **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

# Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

## Waste disposal number of waste from residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and

sealants containing organic solvents or other dangerous substances

Classified as hazardous waste.

# Contaminated packaging

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

# **SECTION 14: Transport information**

Land transport (ADR/RID)

**14.1. UN number:** UN3267

**14.2. UN proper shipping name:** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.

(3-Aminomethyl-3,5,5-trimethylcyclohexylamine, Trimethylhexane-1,6-diamine)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8



Classification code:

Print date: 17.07.2013 GB - EN Page 6 of 8



TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 17.07.2013 Revision No: 1,01

**TIP TOP COROFLAKE 60 B** 

00359-1036

Limited quantity: 5 L / 30 kg

Transport category: 3
Hazard No: 80
Tunnel restriction code: E

Inland waterways transport (ADN)

<u>14.1. UN number:</u> UN3267

**14.2. UN** proper shipping name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.

(3-Aminomethyl-3,5,5-trimethylcyclohexylamine, Trimethylhexane-1,6-diamine)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8

8

Classification code: C7 Limited quantity: 5 L / 30 kg

Marine transport (IMDG)

14.1. UN number: UN3267

14.2. UN proper shipping name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (isophoronediamine and

trimethylhexane diamine)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8



Limited quantity: 5 L / 30 kg EmS: F-A. S-B

Air transport (ICAO)

UN/ID number: UN3267

14.2. UN proper shipping name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (isophoronediamine and

trimethylhexane diamine)

14.3. Transport hazard class(es):814.4. Packing group:III

Hazard label:



Limited quantity Passenger: Y841 / 1 L
IATA-packing instructions - Passenger: 852
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 856

IATA-max. quantity - Cargo: **14.5. Environmental hazards** 

Dangerous for the environment: no

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

The transport takes place only in approved and appropriate packaging.

## **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU** regulatory information

Print date: 17.07.2013 GB - EN Page 7 of 8

60 L



TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 17.07.2013 Revision No: 1,01



00359-1036

1999/13/EC (VOC): 0 %

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment

restrictions for child bearing mothers and nursing.

Water contaminating class (D): 2 - water contaminating

#### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

# **SECTION 16: Other information**

## Full text of R phrases referred to under Sections 2 and 3

20/22 Harmful by inhalation and if swallowed.
21/22 Harmful in contact with skin and if swallowed.
22 Harmful if swallowed.

34 Causes burns

36/38 Irritating to eyes and skin.

43 May cause sensitisation by skin contact.

Toxic to aquatic organisms.Harmful to aquatic organisms.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

53 May cause long-term adverse effects in the aquatic environment.

61 May cause harm to the unborn child.

### Full text of H statements referred to under Sections 2 and 3

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H360D May damage the unborn child.

H411 Toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

# **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

 Print date: 17.07.2013
 GB - EN
 Page 8 of 8