TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 22.11.2013 Revision No: 1,00



00359-1176



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP COROPUR ZINC M

Art.-No

580 0016, 580 0023, 580 0030

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Coating component

1.3. Details of the supplier of the safety data sheet

TIP TOP Oberflaechenschutz Elbe GmbH

Heuweg 4

D-06886 Wittenberg

Telephone: +49(0)3491/635-50Telefax: +49(0)3491/635-552Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: Xi - Irritant, N - Dangerous for the environment

R phrases: Flammable.

May cause sensitisation by skin contact.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

GHS classification

Hazard categories:

Flammable liquid: Flam. Liq. 3

Respiratory/skin sensitization: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Acute 1 Hazardous to the aquatic environment: Aquatic Chronic 1

Hazard Statements:

Flammable liquid and vapour.

May cause an allergic skin reaction.

Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Pictograms:

GHS02-GHS07-GHS09







Signal word:

word: Warning

Hazardous components which must be listed on the label

Aromatic polyisocyanate prepolymer 4-isocyanatosulphonyltoluene

Hazard statements

H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing vapour.

Print date: 22.11.2013 GB - EN Page 1 of 10

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 22.11.2013 Revision No: 1,00



TIP TOP COROPUR ZINC M

00359-1176

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P273 Avoid release to the environment.

Special labelling of certain mixtures

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3. Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Aromatic polyisocyanate

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
231-175-3	zinc powder - zinc dust (stabilized)	50 - 100 %
7440-66-6	N - Dangerous for the environment R50-53	
030-001-01-9	Aquatic Acute 1, Aquatic Chronic 1; H400 H410	
01-2119467174-37		
918-668-5	Solvent naphta (petroleum)	5 - 10 %
64742-95-6	Xn - Harmful, Xi - Irritant, N - Dangerous for the environment R10-37-51-53-65-66-67	
649-356-00-4	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411	
01-2119455851-35		
215-222-5	Zinc oxide	2,5 - 5 %
1314-13-2	N - Dangerous for the environment R50-53	
030-013-00-7	Aquatic Acute 1, Aquatic Chronic 1; H400 H410	
01-2119463881-32		
203-603-9	2-Methoxy-1-methylethyl acetate	2,5 - 5 %
108-65-6	R10	
607-195-00-7	Flam. Liq. 3; H226	
01-2119475791-29		
215-535-7	Xylene (mixed isomers)	1 - 2,5 %
1330-20-7	Xn - Harmful, Xi - Irritant R10-20/21-38	
601-022-00-9	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H312 H332 H315 H319 H335 H373 H304	
01-2119486136-34		
	Aromatic polyisocyanate prepolymer	1 - 2,5 %
127821-00-5	Xi - Irritant R36-43	
	Eye Irrit. 2, Skin Sens. 1; H319 H317	
223-810-8	4-isocyanatosulphonyltoluene	0,5 - 1 %
4083-64-1	Xi - Irritant R14-36/37/38-42	
615-012-00-7	Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, STOT SE 3; H315 H319 H334 H335	
01-2119980050-47		

Full text of R and H phrases: see Section 16.

Further Information

According to note P to the regulation (EC) no. 1272/2008, "Solvent naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

SECTION 4: First aid measures

4.1. Description of first aid measures

Print date: 22.11.2013 GB - EN Page 2 of 10

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 22.11.2013 Revision No: 1,00



00359-1176

General information

Remove contaminated soaked clothing immediately.

If you feel unwell, seek medical advice.

Take away from danger area and lay down affected person.

In case of the person being unconscious put him/her in a stable side position.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

Refer for medical treatment.

If patient is not breathing, apply artificial respiration.

After contact with skin

Wash off with soap and plenty of water.

Consult a doctor if skin irritation persists.

Do not use solvents or thinners.

After contact with eyes

Remove contact lens.

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Extinguishing media which must not be used for safety reasons

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Cool containers at risk with water spray jet.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Vapours are heavier than air and spread along ground.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Inform competent authority about release into the sewerage, ground or into waters.



TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 22.11.2013 Revision No: 1,00



00359-1176



6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

Container should not be gas-tight closed.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Keep a good ventilation and air-exhaust at the place of work.

Vapours are heavier than air and spread along ground.

Avoid contact with the skin and the eyes.

When using, do not eat, drink or smoke.

Do not empty container under pressure. No pressure tank!

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion protection rules.

Protect from heat and direct solar radiation.

Storage temperature between 15°C to 30°C

Advice on storage compatibility

Incompatible with:

Oxidizing agents

Acids and bases.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Coating component

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
-	Isocyanates, all (as -NCO) Except methyl isocyanate	-	0.02		TWA (8 h)	WEL
		-	0.07		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 22.11.2013 Revision No: 1,00



00359-1176



Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

8.2. Exposure controls

Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothing before re-use.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 141).

Hand protection

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove < Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Eye protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Skin protection

Long sleeved clothing (EN 368).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Various
Odour: characteristic

Test method

Changes in the physical state

Flash point: 39 °C DIN 53213

Lower explosion limits:1,1 vol. %Upper explosion limits:10,8 vol. %Ignition temperature:180 °CVapour pressure:0,78 hPa

(at 20 °C)

Density (at 20 °C): 2,59 g/cm³ Water solubility: Immiscible

(at 20 °C)

Viscosity / dynamic: 500 - 700 mPa·s Viscosity / kinematic: > 20,5 mm²/s

(at 40 °C)

Solvent content: 15 %

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

Print date: 22.11.2013 GB - EN Page 5 of 10

TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 22.11.2013 Revision No: 1,00



00359-1176

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Heating can release vapours which can be ignited.

Vapour/air-mixtures are explosive at intense warming.

10.5. Incompatible materials

Strong oxidizing agents

Strong acids and strong bases.

10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

Hydrogen cyanide gas., Isocyanates

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

No toxicological data available.

Irritation and corrosivity

Skin irritation: Not classified. Eye irritation: Not classified.

Sensitising effects

May cause an allergic skin reaction.

Severe effects after repeated or prolonged exposure

STOT - Single exposure: Not classified. STOT - Repeated exposure: Not classified.

Aspiration hazard: Not classified.

Carcinogenic/mutagenic/toxic effects for reproduction

Carcinogenicity: Not classified. Mutagenicity: Not classified. Teratogenicity: Not classified.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Empirical data on effects on humans

Irritating to respiratory system.

Limited evidence of a carcinogenic effect.

May cause sensitization by inhalation and skin contact.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Inhalation of high concentrations may cause injuries to liver, kidneys and central nervous system.

A longer or repeated contact my lead to irritation of eyes and mucous membranes.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product. With hypersensitive people, reactions as cough or difficulty of breathing may appear even with tiny concentrations of isocyanates; therefore keep room aerated and ventilated.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Very toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.





TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 22.11.2013 Revision No: 1,00



00359-1176

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

Waste disposal number of waste from residues/unused products

080111

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other dangerous substances

Classified as hazardous waste.

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

 14.1. UN number:
 1263

 14.2. UN proper shipping name:
 Paint

 14.3. Transport hazard class(es):
 3

 14.4. Packing group:
 III

 Hazard label:
 3



Classification code: F1

Limited quantity: 5 L / 30 kg

Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number:126314.2. UN proper shipping name:Paint14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1

Limited quantity: 5 L / 30 kg

Marine transport (IMDG)

<u>14.1. UN number:</u> 1263



TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 22.11.2013 Revision No: 1,00



00359-1176

14.2. UN proper shipping name:Paint14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Marine pollutant: Yes
Limited quantity: 5 L / 30 kg
EmS: F-E, S-E

Air transport (ICAO)

UN/ID number:126314.2. UN proper shipping name:Paint14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Limited quantity Passenger: Y344 / 10 L

IATA-packing instructions - Passenger:355IATA-max. quantity - Passenger:60 LIATA-packing instructions - Cargo:366IATA-max. quantity - Cargo:220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

1999/13/EC (VOC): < 20 %

396 g/l

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment

restrictions for child bearing mothers and nursing.

Additional information

Chemical prohibition regulation consider.

SECTION 16: Other information

Changes

Changes in chapter: 2, 3, 4, 6, 7, 8, 9, 10, 11, 12, 14, 15




TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 22.11.2013 Revision No: 1,00



00359-1176



ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC = Code International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

VOC = Volatile organic compound

STOT SE = Specific target organ toxicity single exposure

STOT RE = Specific target organ toxicity repeated exposure

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

bw = body weight

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Full text of R phrases referred to under Sections 2 and 3

10 Flammable.

14 Reacts violently with water.

20/21 Harmful by inhalation and in contact with skin.

36 Irritating to eyes.

36/37/38 Irritating to eyes, respiratory system and skin.

37 Irritating to respiratory system.

38 Irritating to skin.

42 May cause sensitisation by inhalation.43 May cause sensitisation by skin contact.

Very toxic to aquatic organisms.

50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

51 Toxic to aquatic organisms.

53 May cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

Full text of H statements referred to under Sections 2 and 3

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.





TIP TOP Oberflaechenschutz Elbe GmbH

Revision date: 22.11.2013 Revision No: 1,00



00359-1176



Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)