
REMA TIP TOP GmbH

Revision date: 09.03.2010 Revision no.: 1,16



00156-0074



## 1. Identification of the substance/preparation and of the company/undertaking

#### Identification of the substance or preparation

TIP TOP INNERLINER SEALER, free of chlorinated hydrocarbons and aromatic hydrocarbons

#### Art.-No.:

515 9004, 515 9011, 515 9028, 515 9035, 515 9042, 515 9058, 515 9059

#### Use of the substance/preparation

Adhesive

#### Company/undertaking identification

REMA TIP TOP GmbH Gruber Straße 63 D-85586 Poing

Telephone:

++49 (0) 8121 / 707 - 0

#### Responsible Department:

Emergency telephone: ++49 (0) 6132 / 84463 (GBK Gefahrgut Buero GmbH, Ingelheim)

Responsible for the safety data sheet: sds@gbk-ingelheim.de

## 2. Hazards identification

#### Classification

Indications of danger: Highly flammable, Irritant, Dangerous for the environment

R-phrases:

Highly flammable. Irritating to skin.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

#### Explication of special hazards for human health and environment

Defatting to skin.

#### 3. Composition/information on ingredients

## Chemical characterization (Mixture)

Preparation solved in petroleum spirit

#### **Hazardous components**

	EC-No.	CAS-No.	Chemical name	Quantity	Classification
	265-151-9	64742-49-0	Naphtha (petroleum)	< 70 %	F, N, Xi, Xn R11-38-51-53-65-67
I	215-222-5	1314-13-2	zinc oxide	< 1 %	N R50-53

Full text of each relevant R phrase can be found in heading 16.

#### **Further Information**

According to note P to the regulation (EC) no. 1272/2008, "Naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

#### 4. First aid measures

#### **General information**

GB - EN Page 1 of 7

REMA TIP TOP GmbH

Revision date: 09.03.2010 Revision no.: 1,16



00156-0074

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Take away from danger area and lay down affected person.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours.

Seek medical treatment immediately.

#### After contact with skin

Wash off with soap and plenty of water.

Treat subsequently with skin cream.

Consult a doctor if skin irritation persists.

#### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Summon a doctor immediately.

#### After ingestion

Induce vomiting only upon the advice of a physician.

Attention. Beware, danger of aspiration.

Do not induce vomiting.

Summon a doctor immediately.

#### 5. Fire-fighting measures

#### Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

# Extinguishing media which must not be used for safety reasons

Full water jet.

# Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases

Fire may produce:

Carbon monoxide, carbon dioxide and sulphur oxides.

## Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Protective suit.

#### **Additional information**

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

# 6. Accidental release measures

#### Personal precautions

In case of vapour formation use respirator.

Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

Keep away sources of ignition.

## **Environmental precautions**

Do not discharge into the drains/surface waters/groundwater.

TOP

GB - EN Page 2 of 7

REMA TIP TOP GmbH

Revision date: 09.03.2010 Revision no.: 1,16



00156-0074



Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

## 7. Handling and storage

#### Handling

#### Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Use only in thoroughly ventilated areas.

## Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

#### **Storage**

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

#### Advice on storage compatibility

Incompatible with oxidizing agents.

## Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

#### 8. Exposure controls/personal protection

# **Exposure limit values**

## **Exposure limits (EH40)**

CAS-No.	Chemical name	ml/m³	mg/m³	F/ml	Category	Origin
1314-13-2	Zinc oxide, fume (OLD)	-	5		TWA (8 h)	OES
		-	10		STEL (15 min)	OES

#### Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

## Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Treat subsequently with skin cream.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

#### Respiratory protection


In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

GB - EN Page 3 of 7



REMA TIP TOP GmbH

Revision date: 09.03.2010 Revision no.: 1,16



00156-0074



Protective gloves resistant to chemicals made off nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril 735> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN

374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

#### Eye protection

Tightly fitting goggles

#### Skin protection

Solvent-resistant apron.

## 9. Physical and chemical properties

# **General information**

Physical state : Liquid Colour : Black

Odour: Hydrocarbon-like

## Important health, safety and environmental information

## Changes in the physical state

Boiling point: 60 - 95 °C

Flash point: < - 25 °C

Lower explosion limits: 1,1 vol. %

Upper explosion limits: 7 vol. %

Vapour pressure: 180 hPa

(at 20 °C)

Density: 0,83 g/cm³
Water solubility: Immiscible

(at 20 °C)

Viscosity / dynamic : 6000 mPa·s

Solvent content

60 - 70 %

#### **Other information**

Ignition temperature : 260 °C

# 10. Stability and reactivity

#### Conditions to avoid

To avoid thermal decomposition, do not overheat.

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

#### Materials to avoid

Oxidizing agents.

# Hazardous decomposition products

Carbon monoxide, carbon dioxide, sulphur oxides.

## Additional information

No decomposition if stored and applied as directed.

#### 11. Toxicological information

GB - EN Page 4 of 7

REMA TIP TOP GmbH

Revision date: 09.03.2010 Revision no.: 1,16



00156-0074



#### Empirical data on effects on humans

Irritating to skin.

Vapours may cause drowsiness and dizziness.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Contact with eyes may cause irritation.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

#### 12. Ecological information

#### **Further information**

Do not flush into surface water or sanitary sewer system.

Low hazard to waters.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### 13. Disposal considerations

## Advice on disposal

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

# Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances

Classified as hazardous waste.

#### Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

1133

Packaging that cannot be cleaned should be disposed of like the product.

## 14. Transport information

## **Land transport (ADR/RID)**

or manipor .	
ADR/RID class :	3
Classification code :	F1
Warning plate	
Hazard-no.:	33
Hazard label :	3

Hazard label: 3
ADR/RID packing group: II
Limited quantity: LQ 6

# Description of the goods


Adhesives

UN number :

GB - EN Page 5 of 7

REMA TIP TOP GmbH

Revision date: 09.03.2010 Revision no.: 1,16



00156-0074



LQ 6: combination packaging: 5 I / 30 kg (total gross mass); trays: 1 I / 20 kg (total gross mass).

Tunnel restriction code: D/E

Transport category: 2

Additional label with symbol "fish and tree" according to subsection 5.2.1.8.3. ADR for single packagings and inner packagings with > 5 kg or 5 L, transition period ends 31.12.2010.

**Marine transport** 

 UN number :
 1133

 IMDG code :
 3

 Marine pollutant :
 No

 Hazard label :
 3

 IMDG packing group :
 II

EmS: F-E; S-D Limited quantity: 5 L / 30 kg

## **Description of the goods**

**ADHESIVES** 

#### Other applicable information (marine transport)

Limited quantities (section 3.4): combination packaging: 5 I / 30 kg (total gross mass); trays: 5 I / 20 kg (total gross mass).

Additional label with symbol "fish and tree" according to subsection 5.2.1. IMDG Code for single packagings and inner packagings with > 5 kg or 5 L.

Air transport

UN/ID number: 1133 ICAO/IATA-DGR: 3 Hazard label: 3 ICAO packing group: II

Limited quantity Passenger: Y305 / 1 L
IATA-packing instructions - Passenger: 305
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 307
IATA-max. quantity - Cargo: 60 L

**Description of the goods** 

**ADHESIVES** 

#### 15. Regulatory information

## Labelling

## Additional advice on labelling

According to EC-regulations the product is to be labelled as follows:

Danger symbols: F - Highly flammable; Xi - Irritant; N - Dangerous for the environment







F - Highly flammable

Xi - Irritant

N - Dangerous for the environment

R phrases

11 Highly flammable.

GB - EN Page 6 of 7

**REMATIP TOP GmbH** 

Revision date: 09.03.2010 Revision no.: 1,16



# TIP TOP INNERLINER SEALER, free of chlorinated hydrocarbons and aromatic hydrocarbons

00156-0074

38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

S phrases

16 Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

This material and its container must be disposed of in a safe way.

Avoid release to the environment. Refer to special instructions / Safety data sheets.

**EU regulatory information** 

1999/13/EC (VOC): < 70 %

**National regulatory information** 

Employment restrictions: Observe employment restrictions for young people. Observe

employment restrictions for child bearing mothers and nursing.

Water contaminating class (D): 1 - slightly water contaminating

## 16. Other information

#### Full text of R-phrases referred to under sections 2 and 3

Highly flammable.Irritating to skin.

Very toxic to aquatic organisms.

Toxic to aquatic organisms.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

May cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed.
Vapours may cause drowsiness and dizziness.

#### **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

GB - EN Page 7 of 7