REMA TIP TOP GmbH

Revision date: 29.06.2009 Revision no.: 1.23



TIP TOP LIQUID BUFFER SPRAY, free of chlorinated and aromatic hydrocarbons

00156-0090

1. Identification of the substance/mixture and of the company/undertaking

Identification of the substance or mixture

TIP TOP LIQUID BUFFER SPRAY, free of chlorinated and aromatic hydrocarbons

Art.-No.

505 9692

Use of the substance/mixture

Cleaning agent

Company/undertaking identification

REMA TIP TOP GmbH Gruber Strasse 63 D-85586 Poing

Telephone:

++49 (0) 8121 / 707 - 0

Responsible Department:

Emergency telephone :++49 (0) 6132 / 84463 (GBK Gefahrgut Buero GmbH, Ingelheim)

Responsible for the safety data sheet: sds@gbk-ingelheim.de

2. Hazards identification

Classification

Indications of danger: Extremely flammable, Irritant, Dangerous for the environment

R-phrases:

Extremely flammable.

Irritating to skin.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

Explication of special hazards for human health and environment

In use, may form flammable/explosive vapour-air mixture.

Heating will cause pressure rise with risk of bursting.

3. Composition/information on ingredients

Chemical characterization (Mixture)

Preparation with aliphatic hydrocarbons (free of aromatic hydrocarbons)

Hazardous components

EC No.	CAS No.	Chemical name	Quantity	Classification		
265-151-9	64742-49-0	Naphtha (petroleum)	> 70 %	F, N, Xi, Xn R11-38-51-53-65-67		
200-827-9	74-98-6	Propane	5 - 10 %	F+ R12		
203-448-7	106-97-8	Butane	5 - 10 %	F+ R12		
205-500-4	141-78-6	Ethyl acetate	1 - 5 %	F, Xi R11-36-66-67		

Full text of each relevant R phrase can be found in heading 16.

Further Information

According to note P to the regulation (EC) no. 1272/2008, "Naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

4. First aid measures

General information

Remove contaminated soaked clothing immediately.

Take away from danger area and lay down affected person.

GB - EN Page 1 of 7

REMATIP TOP GmbH

Revision date: 29.06.2009 Revision no.: 1.23



TIP TOP LIQUID BUFFER SPRAY, free of chlorinated and aromatic hydrocarbons

00156-0090

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

In the event of symptoms refer for medical treatment.

After contact with skin

Wash off with soap and plenty of water.

Consult a doctor if skin irritation persists.

After contact with eyes

If eye irritation persists, consult a specialist.

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

After ingestion

Induce vomiting only upon the advice of a physician.

Attention. Beware, danger of aspiration.

Do not induce vomiting.

Summon a doctor immediately.

5. Fire-fighting measures

Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

Extinguishing media which must not be used for safety reasons

Full water jet.

Special exposure hazards arising from substance or mixture itself, combustion products, resulting gases

Fire may produce:

Carbon monoxide and carbon dioxide.

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Protective suit.

Additional information

Heating will cause pressure rise with risk of bursting.

Cool containers at risk with water spray jet.

Vapours can form an explosive mixture with air.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

6. Accidental release measures

Personal precautions

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

Methods for cleaning up/taking up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

7. Handling and storage

Handling

Advice on safe handling

Avoid contact with the skin and the eyes.

Use only in thoroughly ventilated areas.

GB - EN Page 2 of 7

REMA TIP TOP GmbH

Revision date: 29.06.2009 Revision no.: 1.23



TIP TOP LIQUID BUFFER SPRAY, free of chlorinated and aromatic hydrocarbons

00156-0090

Advice on protection against fire and explosion

Do not smoke - volatile.

Keep away from open flames, hot surfaces and sources of ignition.

Pay attention to anti-explosion rules.

Do not spray on a naked flame or any other incandescent material.

Storage

Requirements for storage rooms and vessels

Protect against direct sun radiation.

Keep container tightly closed.

Use only in well-ventilated areas.

Advice on storage compatibility

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

8. Exposure controls/personal protection

Exposure limit values

Exposure limits (EH40)

CAS No.	Chemical name	ml/m³	mg/m³	F/ml	Category	Origin	
106-97-8	Butane	600	1450		TWA (8 h)	WEL	
		750	1810		STEL (15 min)	WEL	
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL	
		400	-		STEL (15 min)	WEL	
	,			1			1

Exposure controls

Protective and hygiene measures

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Remove and wash contaminated clothes before re-use.

Do not breath vapours or spray mist.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type AX).

Hand protection

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove < Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Eve protection

Safety goggles with side protection.

Skin protection

Long sleeved clothing.

9. Physical and chemical properties

General information

Physical state: Aerosol
Colour: Colourless
Odour: Hydrocarbon-like

GB - EN Page 3 of 7

REMATIP TOP GmbH

Revision date: 29.06.2009 Revision no.: 1,23



TIP TOP LIQUID BUFFER SPRAY, free of chlorinated and aromatic hydrocarbons

00156-0090

Important health, safety and environmental information

Test method

0,66 g/cm³

Changes in the physical state

Flash point: $-60 \,^{\circ}\text{C} \,^{*})$ Lower explosion limits: $1,4 \, \text{vol.} \,^{\%}$ Upper explosion limits: $32 \, \text{vol.} \,^{\%}$ Ignition temperature: $510 \,^{\circ}\text{C} \,^{*})$ Vapour pressure: $(\text{at } 20 \,^{\circ}\text{C})$

-

Water solubility: Immiscible (at 20 °C)

Solvent content: > 65 %

Other information

Density (at 20 °C):

*) Propellant

10. Stability and reactivity

Conditions to avoid

Vapours may form explosive mixture with air.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Heating will cause pressure rise with risk of bursting.

Materials to avoid

Oxidizing agents.

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Further information

No decomposition if stored and applied as directed.

11. Toxicological information

Empirical data on effects on humans

Irritating to skin.

Vapours may cause drowsiness and dizziness.

High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

12. Ecological information

Further information

Do not flush into surface water or sanitary sewer system.

Low hazard to waters.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. Disposal considerations

Advice on disposal

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

Waste disposal number of waste from residues/unused products

GB - EN Page 4 of 7

REMA TIP TOP GmbH

Revision date: 29.06.2009 Revision no.: 1.23



TIP TOP LIQUID BUFFER SPRAY, free of chlorinated and aromatic hydrocarbons

00156-0090

150111

WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

Classified as hazardous waste.

Contaminated packaging

Offer empty spray cans to an established disposal company.

14. Transport information

Land transport (ADR/RID)

UN number: 1950

Description of the goods

AEROSOLS
ADR/RID class: 2
Classification code: 5F

Warning plate

Hazard label: 2.1



ADR/RID packing group: -

Limited quantity: LQ 2

Other applicable information (land transport)

LQ 2: combination packaging: 1 I / 30 kg (total gross mass); trays: 1 I / 20 kg (total gross mass).

Tunnel restriction code: D Transport category: 2

Additional label with symbol "fish and tree" according to subsection 5.2.1.8.3. ADR for single packagings and inner packagings with > 5 kg or 5 L, transition period ends 31.12.2010.

Marine transport

UN number: 1950

Description of the goods

AEROSOLS

IMDG code:2Marine pollutant:NoHazard label:2.1



IMDG packing group:

EmS: F-D; S-U Limited quantity: 1 L / 30 kg

Other applicable information (marine transport)

Limited quantities (chapter 3.4): combination packaging: 1 I / 30 kg (total gross mass); trays: 1 I / 20 kg (total gross mass)

Additional label with symbol "fish and tree" according to subsection 5.2.1. IMDG Code for single packagings and inner packagings with > 5 kg or 5 L.

Air transport

UN/ID number: 1950

Description of the goods

AEROSOLS FLAMMABLE

ICAO/IATA-DGR: 2.1 Hazard label: 2.1

GB - EN Page 5 of 7

REMA TIP TOP GmbH

Revision date: 29.06.2009 Revision no.: 1,23



TIP TOP LIQUID BUFFER SPRAY, free of chlorinated and aromatic hydrocarbons

00156-0090



ICAO packing group:

Limited quantity Passenger: Y203 / 30 kg

IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

15. Regulatory information

Labelling

According to EC-regulations the product is to be labelled as follows:

Danger symbols: F+ - Extremely flammable; Xi - Irritant; N - Dangerous for the environment



F+ - Extremely flammable



Xi - Irritant



N - Dangerous for the environment

R phrases

12 Extremely flammable.
38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

S phrases

09 Keep container in a well-ventilated place.

23 Do not breathe spray.

This material and its container must be disposed of in a safe way.

51 Use only in well-ventilated areas.

Avoid release to the environment. Refer to special instructions / Safety data sheets.

Special labelling of certain mixtures

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding

50 °C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

EU regulatory information

1999/13/EC (VOC): 100 %

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe

employment restrictions for child bearing mothers and nursing.

Water contaminating class (D): 1 - slightly water contaminating

16. Other information

Full text of R-phrases referred to under sections 2 and 3

11 Highly flammable.

12 Extremely flammable.

36 Irritating to eyes.38 Irritating to skin.

51 Toxic to aquatic organisms.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

GB - EN Page 6 of 7

REMATIP TOP GmbH





TIP TOP LIQUID BUFFER SPRAY, free of chlorinated and aromatic hydrocarbons

00156-0090

environment.

May cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed.

Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

GB - EN Page 7 of 7