REMATIP TOP GmbH

Revision date: 19.07.2010 Revision no.: 1,15



00156-0122



1. Identification of the substance/preparation and of the company/undertaking

Identification of the substance or preparation

TIP TOP REMACLAVE SOLUTION

Art.-No.:

538 1600, 538 1610, 538 1620

Use of the substance/preparation

Adhesive

Company/undertaking identification

REMA TIP TOP GmbH Gruber Straße 63 D-85586 Poing

Telephone:

++49 (0) 8121 / 707 - 0

Responsible Department:

Emergency telephone :++49 (0) 6132 / 84463 (GBK Gefahrgut Buero GmbH, Ingelheim)

Responsible for the safety data sheet: sds@gbk-ingelheim.de

2. Hazards identification

Classification

Indications of danger: Highly flammable, Irritant, Dangerous for the environment

R-phrases:

Highly flammable. Irritating to skin.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

3. Composition/information on ingredients

Chemical characterization (Mixture)

Preparation with aromatic hydrocarbons

Hazardous components

EC-No.	CAS-No.	Chemical name	Quantity	Classification
265-151-9	64742-49-0	Naphtha (petroleum)	< 90 %	F, N, Xi, Xn R11-38-51-53-65-67
203-777-6	110-54-3	n-Hexane		F, Repr. Cat. 3, Xn, Xi, N R11-62-48/20-65-38-67-51-53
215-222-5	1314-13-2	Zinc oxide	< 2,5 %	N R50-53

Full text of each relevant R phrase can be found in heading 16.

Further Information

According to note P to the regulation (EC) no. 1272/2008, "Naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

4. First aid measures

General information

GB - EN Page 1 of 7

REMATIP TOP GmbH

Revision date: 19.07.2010 Revision no.: 1,15



00156-0122

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water.

Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

The decision whether to induce vomiting or not is to be taken by a physician.

Advice to doctor

Attention. Beware, danger of aspiration.

5. Fire-fighting measures

Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

Extinguishing media which must not be used for safety reasons

Full water jet.

Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases

Fire may produce:

Carbon monoxide and carbon dioxide.

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Protective suit.

Additional information

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

6. Accidental release measures

Personal precautions

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater.



GB - EN Page 2 of 7

REMATIP TOP GmbH

Revision date: 19.07.2010 Revision no.: 1,15



00156-0122



Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Additional information

Clean contaminated surface thoroughly.

7. Handling and storage

Handling

Advice on safe handling

Keep container tightly closed.

Use only in area provided with appropriate exhaust ventilation.

(in case of higher concentration).

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

Advice on protection against fire and explosion

Keep product and empty container away from heat and sources of ignition.

Pay attention to anti-explosion rules.

Do not smoke.

Take precautionary measures against static discharges (earthing (grounding)) at pouring).

Storage

Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

Keep away from heat and sources of ignition.

Advice on storage compatibility

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

8. Exposure controls/personal protection

Exposure limit values

Exposure limits (EH40)

CAS-No.	Chemical name	ml/m³	mg/m³	F/ml	Category	Origin
1314-13-2	Zinc oxide, fume (OLD)	-	5		TWA (8 h)	OES
		-	10		STEL (15 min)	OES
110-54-3	i-Hexane	20	72		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

Pay attention to explosion protection guidelines.

Protective and hygiene measures

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

GB - EN Page 3 of 7



REMATIP TOP GmbH

Revision date: 19.07.2010 Revision no.: 1,15



00156-0122

Hand protection

Protective gloves resistant to chemicals made off viton, Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove < Vitoject 890> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN

374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Eye protection

Tightly fitting goggles.

Eye wash bottle with pure water.

Skin protection

Long sleeved clothing.

Remove and wash contaminated clothing before re-use.

9. Physical and chemical properties

General information

Physical state : Liquid Colour : Black

Odour: Hydrocarbon-like

Important health, safety and environmental information

Changes in the physical state

Boiling point: 107 - 137 °C *)
Flash point: 1 °C *)
Lower explosion limits: 0,9 vol. % *)
Upper explosion limits: 6,8 vol. % *)
Vapour pressure: 35 hPa *)

(at 20 °C)

Density (at 20 °C):

Water solubility:

0,8 g/cm³

Immiscible

(at 20 °C)

Flow time: 30 s Flow time in a 6 mm cup

(at 20 °C)

Solvent content

< 90 %

Other information

Ignition temperature : 310 °C *)

*) Naphtha (petroleum)

10. Stability and reactivity

Conditions to avoid

To avoid thermal decomposition, do not overheat.

Vapours may form explosive mixture with air.

Materials to avoid

Strong oxidizing agents.

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Additional information

No decomposition if stored and applied as directed.

GB - EN Page 4 of 7



REMATIP TOP GmbH

Revision date: 19.07.2010 Revision no.: 1,15

TIP TOP REMACLAVE SOLUTION

00156-0122



11. Toxicological information

Empirical data on effects on humans

Irritating to skin.

Vapours may cause drowsiness and dizziness.

Contact with eyes may cause irritation.

Inhalation of vapours in high concentration can cause narcotic effects.

Inhalation of high vapour concentration may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Attention. Beware, danger of aspiration!

12. Ecological information

Further information

Do not flush into surface water or sanitary sewer system.

Low hazard to waters.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. Disposal considerations

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances

Classified as hazardous waste.

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

14. Transport information

Land transport (ADR/RID)

UN number: 1133
ADR/RID class: 3
Classification code: F1
Warning plate
Hazard-no.: 33
Hazard label: 3

ADR/RID packing group : II
Limited quantity : LQ6

GB - EN Page 5 of 7

REMATIP TOP GmbH

Revision date: 19.07.2010 Revision no.: 1,15



00156-0122

Description of the goods

Adhesives

Other applicable information (land transport)

LQ 6: combination packaging: 5 l / 30 kg (total gross mass); trays: 1 l / 20 kg (total gross mass).

Tunnel restriction code: D/E Transport category: 2

Additional label with symbol "fish and tree" according to subsection 5.2.1.8.3. ADR for single packagings and inner packagings with > 5 kg or 5 L, transition period ends 31.12.2010.

Marine transport

UN number : 1133 IMDG code : 3 Hazard label : 3 IMDG packing group : II

EmS: F-E, S-D Limited quantity: 5 L / 30 kg

Description of the goods

Adhesives

Other applicable information (marine transport)

Limited quantities (section 3.4): combination packaging: 5 l / 30 kg (total gross mass); trays: 5 l / 20 kg (total gross mass).

Additional label with symbol "fish and tree" according to subsection 5.2.1. IMDG Code for single packagings and inner packagings with > 5 kg or 5 L.

Air transport

UN/ID number: 1133
ICAO/IATA-DGR: 3
Hazard label: 3
ICAO packing group: II

Limited quantity Passenger: Y305 / 1 L
IATA-packing instructions - Passenger: 305
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 307
IATA-max. quantity - Cargo: 60 L

Description of the goods

Adhesives

15. Regulatory information

Labelling

Additional advice on labelling

According to EC-regulations the product is to be labelled as follows:

Danger symbols : F - Highly flammable; Xi - Irritant; N - Dangerous for the environment







Xi - Irritant



N - Dangerous for the environment

GB - EN Page 6 of 7



REMATIP TOP GmbH

Revision date: 19.07.2010 Revision no.: 1,15



00156-0122

R phrases

Highly flammable.Irritating to skin.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

S phrases

Do not breathe vapour.Avoid contact with skin.

This material and its container must be disposed of as hazardous waste.

61 Avoid release to the environment. Refer to special instructions / Safety data sheets.

EU regulatory information

1999/13/EC (VOC): < 90 %

National regulatory information

Employment restrictions : Observe employment restrictions for young people. Observe

employment restrictions for child bearing mothers and nursing.

Water contaminating class (D): 1 - slightly water contaminating

16. Other information

Full text of R-phrases referred to under sections 2 and 3

Highly flammable. 38 Irritating to skin.

48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Very toxic to aquatic organisms.Toxic to aquatic organisms.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

May cause long-term adverse effects in the aquatic environment.

62 Possible risk of impaired fertility.

Harmful: may cause lung damage if swallowed.
Vapours may cause drowsiness and dizziness.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

GB - EN Page 7 of 7

