

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

TIP TOP SOLUTION REMACLAVE

Art.-No.

538 1600, 538 1610, 538 1620, 538 1630

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

adhesive

### 1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG  
Street: Gruber Strasse 63  
Place: D-85586 Poing  
Telephone: +49 (0) 8121 / 707 - 0  
Verantwortlich für das Sicherheitsdatenblatt: sds@gbk-ingelheim.de

### 1.4. Emergency telephone

number: INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24  
24

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Indications of danger: F - Highly flammable, N - Dangerous for the environment

R phrases:

Highly flammable.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

### GHS classification

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

Hazardous components which must be listed on the label

Naphtha (petroleum) [Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics]

Signal word: Danger

Pictograms: GHS02-GHS07-GHS09



### Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P273	Avoid release to the environment.

**Special labelling of certain mixtures**

EUH208 Contains N-Phenyl-naphtylamine . May produce an allergic reaction.

**2.3. Other hazards**

Vapours may form explosive mixture with air.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Preparation with aromatic hydrocarbons

**Hazardous components**

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
920-750-0	Naphtha (petroleum) [Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics]	< 80 %
64742-49-0	F - Highly flammable, Xn - Harmful, Xi - Irritant, N - Dangerous for the environment R11-38-51-53-65-67	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	
01-2119473851-33		
215-222-5	Zinc oxide	< 2,5 %
1314-13-2	N - Dangerous for the environment R50-53	
030-013-00-7	Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1 (M-Factor = 1); H400 H410	
01-2119463881-32		
201-983-0	N-Phenyl-naphtylamine	< 1 %
90-30-2	Xn - Harmful, N - Dangerous for the environment R22-43-50-53	
	Acute Tox. 4, Skin Sens. 1, STOT RE 2, Aquatic Chronic 1 (M-Factor = 1); H302 H317 H373 H410	
01-2119488704-27		

Full text of R-, H- and EUH-phrases: see section 16.

**Further Information**

According to note P to the regulation (EC) no. 1272/2008, "Naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.  
In the event of persistent symptoms receive medical treatment.  
Take away from danger area and lay down affected person.

**After inhalation**

Move to fresh air in case of accidental inhalation of vapours.  
In the event of symptoms refer for medical treatment.

**After contact with skin**

Wash off immediately with soap and plenty of water.

Consult a doctor if skin irritation persists.

**After contact with eyes**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

**After ingestion**

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

The decision whether to induce vomiting or not is to be taken by a physician.

**4.2. Most important symptoms and effects, both acute and delayed**

May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

Attention. Beware, danger of aspiration.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

---

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

**Unsuitable extinguishing media**

Full water jet.

**5.2. Special hazards arising from the substance or mixture**

Fire may produce:

Carbon monoxide and carbon dioxide

**5.3. Advice for firefighters**

Use breathing apparatus with independent air supply.

Protective suit.

**Additional information**

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

In case of vapour formation use respirator.

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

Keep away sources of ignition.

Avoid contact with skin, eyes and clothing.

**6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

**6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

**6.4. Reference to other sections**

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

---

**SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

#### **Advice on safe handling**

Keep container tightly closed.

Use only in area provided with appropriate exhaust ventilation.

(in case of higher concentration).

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 141)

#### **Advice on protection against fire and explosion**

Keep product and empty container away from heat and sources of ignition.

Pay attention to anti-explosion rules.

Do not smoke.

Take precautionary measures against static discharges (earthing (grounding ) at pouring ).

### **7.2. Conditions for safe storage, including any incompatibilities**

#### **Requirements for storage rooms and vessels**

Keep containers tightly closed in a cool, well-ventilated place.

Keep away from heat and sources of ignition.

#### **Advice on storage compatibility**

Incompatible with oxidizing agents.

#### **Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

### **7.3. Specific end use(s)**

adhesive

## **SECTION 8: Exposure controls/personal protection**

### **8.1. Control parameters**

#### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
1333-86-4	Carbon black	-	3.5		TWA (8 h)	WEL
		-	7		STEL (15 min)	WEL

### **8.2. Exposure controls**

#### **Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

Pay attention to explosion protection guidelines.

#### **Protective and hygiene measures**

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

#### **Eye/face protection**

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

#### **Hand protection**

Protective gloves resistant to chemicals made off viton , minimum coat thickness 0,7 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Vitoject 890> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

#### **Skin protection**

Long sleeved clothing (EN 368).

Remove and wash contaminated clothing before re-use.

#### **Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 141).

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	Black	
Odour:	Hydrocarbon-like	
Melting point:	< - 30 °C	*)
Initial boiling point and boiling range:	100 - 140 °C	*)
Flash point:	2 °C	*)
Lower explosion limits:	0,7 vol. %	*)
Upper explosion limits:	8,3 vol. %	*)
Vapour pressure:	10 hPa	*)
(at 20 °C)		
Density (at 20 °C):	0,8 g/cm³	
Water solubility:	Immiscible	
(at 20 °C)		
Ignition temperature:	245 °C	*)
Viscosity / kinematic:	> 20,5 mm²/s	
(at 40 °C)		
Flow time:	30 s	Flow time in a 6 mm cup
(at 20 °C)		
Solvent content:	< 80 %	

### 9.2. Other information

\*) Naphtha (petroleum)

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No decomposition if stored and applied as directed.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Heating can release vapours which can be ignited.

Vapour/air-mixtures are explosive at intense warming.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

No toxicological data available.

Naphtha (petroleum)

LD50/oral/rat: > 5000 mg/kg (Estimated)

LD50/dermal/rabbit: > 2000 mg/kg (Estimated)

LC50/inhalation/rat: > 20 mg/l (Estimated)

#### Irritation and corrosivity

Causes skin irritation.

#### **Sensitising effects**

Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

May cause drowsiness or dizziness. (Naphtha (petroleum) [Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics])

#### **Severe effects after repeated or prolonged exposure**

Based on available data, the classification criteria are not met.

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### **Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### **Practical experience**

#### **Other observations**

Contact with eyes may cause irritation.

Inhalation of vapours in high concentration can cause narcotic effects.

Inhalation of high vapour concentration may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Attention. Beware, danger of aspiration!

---

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

Ecological data are not available.

Toxic to aquatic life with long lasting effects.

### **12.2. Persistence and degradability**

No data available.

### **12.3. Bioaccumulative potential**

No data available.

### **12.4. Mobility in soil**

No data available.

### **12.5. Results of PBT and vPvB assessment**

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

### **12.6. Other adverse effects**

Low hazard to waters.

#### **Further information**

Do not flush into surface water or sanitary sewer system.

---

## **SECTION 13: Disposal considerations**

### **13.1. Waste treatment methods**

#### **Advice on disposal**

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

#### **Waste disposal number of waste from residues/unused products**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances  
Classified as hazardous waste.

#### **Contaminated packaging**

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

## SECTION 14: Transport information

### Land transport (ADR/RID)

**14.1. UN number:** UN1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 5 L / 30 kg  
 Transport category: 2  
 Hazard No: 33  
 Tunnel restriction code: D/E

### Inland waterways transport (ADN)

**14.1. UN number:** UN1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 5 L / 30 kg

### Marine transport (IMDG)

**14.1. UN number:** UN1133  
**14.2. UN proper shipping name:** Adhesives (Naphtha (petroleum))  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Marine pollutant: Yes  
 Limited quantity: 5 L / 30 kg  
 EmS: F-E, S-D

### Air transport (ICAO)

**14.1. UN number:** UN1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Limited quantity Passenger: Y341 / 1 L

IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

#### **14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: yes



#### **14.6. Special precautions for user**

Handle in accordance with good industrial hygiene and safety practice.

#### **14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

The transport takes place only in approved and appropriate packaging.

### **SECTION 15: Regulatory information**

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **EU regulatory information**

1999/13/EC (VOC): < 80 %

##### **National regulatory information**

Employment restrictions: Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing.

#### **15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

### **SECTION 16: Other information**

#### **Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

#### **Relevant R-phrases (Number and full text)**

- |    |   |
|----|---|
| 11 | Highly flammable.   |
| 22 | Harmful if swallowed.   |
| 38 | Irritating to skin.   |
| 43 | May cause sensitisation by skin contact.                        |
| 50 | Very toxic to aquatic organisms.                                |
| 51 | Toxic to aquatic organisms.                                     |
| 53 | May cause long-term adverse effects in the aquatic environment. |
| 65 | Harmful: may cause lung damage if swallowed.                    |





---

67 Vapours may cause drowsiness and dizziness.

**Relevant H- and EUH-phrases (Number and full text)**

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains N-Phenyl-naphtylamine . May produce an allergic reaction.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*