

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP REMACOAT A-80 ISO

Art.-No.

590 2914, 590 2938

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Coating system for protection against wear and corrosion

1.3. Details of the supplier of the safety data sheet

TIP TOP Oberflächenschutz Elbe GmbH

Heuweg 4

D-06886 Wittenberg

Telephone: +49(0)3491/635-50

Telefax: +49(0)3491/635-552

Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24
24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: Xn - Harmful

R phrases:

Harmful by inhalation.

Irritating to eyes, respiratory system and skin.

May cause sensitisation by inhalation and skin contact.

GHS classification

Hazard categories:

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory/skin sensitization: Resp. Sens. 1

Respiratory/skin sensitization: Skin Sens. 1

Carcinogenicity: Carc. 2

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazard Statements:

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause respiratory irritation.

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause damage to organs (Respiratory system) through prolonged or repeated exposure if inhaled.

2.2. Label elements

Pictograms:

GHS07-GHS08



Signal word:

Danger

Hazardous components which must be listed on the label

TIP TOP REMACOAT A-80 ISO

00359-1090

Diphenylmethane-4,4'-diisocyanate
Polypropylene glycol, diphenylmethane diisocyanate polymer
Methyloxirane, polymer with oxirane, ether with oxybis(propanol), polymer with 1,1'-ethylenebis(isocyanatobenzene),
methyloxirane and oxirane
Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate
4,4'-Methylenediphenyl diisocyanate, oligomers

Hazard statements

H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H373 May cause damage to organs (Respiratory system) through prolonged or repeated exposure if inhaled.

Precautionary statements

P260 Do not breathe vapour.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.

Special labelling of certain mixtures

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3. Other hazards

Not known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation with isocyanates

TIP TOP REMACOAT A-80 ISO

00359-1090

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
202-966-0	Diphenylmethane-4,4'-diisocyanate	< 30 %
101-68-8	Carc. Cat. 3, Xn - Harmful, Xi - Irritant R40-20-48/20-36/37/38-42/43	
615-005-00-9	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373	
01-2119457014-47		
	Polypropylene glycol, diphenylmethane diisocyanate polymer	< 30 %
39420-98-9	Carc. Cat. 3, Xn - Harmful, Xi - Irritant R20-36/37/38-40-42/43-48/20	
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, Carc. 2, STOT RE 2; H332 H315 H319 H334 H317 H351 H373	
	Methyloxirane, polymer with oxirane, ether with oxybis(propanol), polymer with 1,1'-ethylenebis(isocyanatobenzene), methyloxirane and oxirane	< 30 %
157937-75-2	Carc. Cat. 3, Xn - Harmful, Xi - Irritant R20-36/37/38-40-42/43-48/20	
	Acute Tox. 4, Eye Irrit. 2, STOT SE 3, Skin Irrit. 2, Carc. 2, Resp. Sens. 1, Skin Sens. 1, STOT RE 2; H332 H319 H335 H315 H351 H334 H317 H373	
203-572-1	Propylene carbonate	< 10 %
108-32-7	Xi - Irritant R36	
607-194-00-1	Eye Irrit. 2; H319	
01-2119537232-48		
	Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate	< 10 %
	Carc. Cat. 3, Xn - Harmful, Xi - Irritant R20-36/37/38-40-42/43-48/20	
	Acute Tox. 4, Eye Irrit. 2, STOT SE 3, Skin Irrit. 2, Carc. 2, Resp. Sens. 1, Skin Sens. 1, STOT RE 2; H332 H319 H335 H315 H351 H334 H317 H373	
01-2119457015-45		
500-040-3	4,4'-Methylenediphenyl diisocyanate, oligomers	< 5 %
25686-28-6	Carc. Cat. 3, Xn - Harmful, Xi - Irritant R20-36/37/38-40-42/43-48/20	
	Acute Tox. 4, Eye Irrit. 2, STOT SE 3, Skin Irrit. 2, Carc. 2, Resp. Sens. 1, Skin Sens. 1, STOT RE 2; H332 H319 H335 H315 H351 H334 H317 H373	
01-2119457013-49		

Full text of R and H phrases: see Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
In the event of persistent symptoms receive medical treatment.

After inhalation

Move to fresh air in case of accidental inhalation of fumes from overheating or combustion.
Refer for medical treatment.

After contact with skin

Remove immediately adhering matter.
Consult a physician.
Wash contaminated skin with plenty of water and soap or with liquid polyethylene glycol.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.
Rinse out mouth thoroughly with water. Never give anything by mouth to an unconscious person.
Summon a doctor immediately.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Harmful if inhaled.

TIP TOP REMACOAT A-80 ISO
00359-1090

Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.
Suspected of causing cancer.
May cause damage to organs through prolonged or repeated exposure if inhaled. (Respiratory system)

4.3. Indication of any immediate medical attention and special treatment needed

Keep under medical supervision for at least 48 hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Extinguishing media which must not be used for safety reasons

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x).

Hydrogen cyanide (HCN)

Isocyanates (NCO).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Container should not be gas-tight closed.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Avoid contact with the skin and the eyes.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours.

When working with spray, exhaustion of air becomes indispensable.

Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.

Advice on storage compatibility

Exothermic reaction with:

Acids and bases.

Water, amines, alcohols

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

7.3. Specific end use(s)

Coating system for protection against wear and corrosion

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.2. Exposure controls****Occupational exposure controls**

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Take off immediately all contaminated clothing.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 141).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

Eye protection

Eye wash bottle with pure water (EN 15154).

Tightly fitting goggles (EN 166).

Skin protection

Long sleeved clothing (EN 368).

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Yellowish
Odour:	Erthy

Test method**Changes in the physical state**

Boiling point:	n.a. (decomposition)
Flash point:	> 100 °C
Lower explosion limits:	n.d.
Ignition temperature:	n.d.
Density (at 25 °C):	1,10 - 1,14 g/cm³

TIP TOP REMACOAT A-80 ISO
00359-1090

Water solubility:	Reacts with water.
Viscosity / dynamic: (at 25 °C)	700 - 1000 mPa·s

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with strong acids and alkalies.

Reacts with: Water, amines, alcohols

10.4. Conditions to avoid

Vapours may form explosive mixture with air.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

10.5. Incompatible materials

Acids and bases.

Water, amines, alcohols

10.6. Hazardous decomposition products

Hydrogen cyanide gas.

Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x).

Isocyanates

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

No toxicological data available.

Harmful if inhaled.

Irritation and corrosivity

Eye irritation: Irritant

Skin irritation: Irritant

Sensitising effects

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Severe effects after repeated or prolonged exposure

STOT - Single exposure: Category 3 [May cause respiratory irritation.]

STOT - Repeated exposure: Category 2 [May cause damage to organs through prolonged or repeated exposure if inhaled.
(Respiratory system)]

Aspiration hazard: Not classified.

Carcinogenic/mutagenic/toxic effects for reproduction

Carcinogenicity: Category 2 [Suspected of causing cancer.]

Mutagenicity: Not classified.

Teratogenicity: Not classified.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Empirical data on effects on humans

With hypersensitive people, reactions as cough or difficulty of breathing may appear even with tiny concentrations of isocyanates; therefore keep room aerated and ventilated.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

TIP TOP REMACOAT A-80 ISO
00359-1090

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

Low hazard to waters.

Further information

In aqueous systems, formation of insoluble and chemically inert (inactive) polyureas.
Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal.
Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances
Classified as hazardous waste.

Contaminated packaging

Contaminated packagings are to be treated like the product itself.
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.
Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Other applicable information

No hazardous material as defined by the transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

1999/13/EC (VOC): 0 %

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

Changes in chapter: 1, 2, 3, 4, 6, 7, 10, 11, 12, 16

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC = Code International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
VOC = Volatile organic compound
STOT SE = Specific target organ toxicity single exposure
STOT RE = Specific target organ toxicity repeated exposure
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative
bw = body weight
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Full text of R phrases referred to under Sections 2 and 3

20 Harmful by inhalation.
36 Irritating to eyes.
36/37/38 Irritating to eyes, respiratory system and skin.
40 Limited evidence of a carcinogenic effect.
42/43 May cause sensitisation by inhalation and skin contact.
48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Full text of H statements referred to under Sections 2 and 3

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs (Respiratory system) through prolonged or repeated exposure if inhaled.
H373 May cause damage to organs through prolonged or repeated exposure.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.
The delivery specifications are contained in the corresponding product sheet.
This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.
(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)