



1. Identification of the substance/preparation and of the company/undertaking

Identification of the substance or preparation

TIP TOP SPECIAL CEMENT BL, free of chlorinated and aromatic hydrocarbons

Art.-No.:

515 9152, 515 9303, 515 9327, 515 9334, 515 9336, 515 9341, 515 9358, 515 9359, 515 9365, 515 9389, 515 9396, 515 9406

Use of the substance/preparation

Adhesive

Company/undertaking identification

REMA TIP TOP GmbH

Gruber Straße 63

D-85586 Poing

Telephone : ++49 (0) 8121 / 707 - 0

Responsible Department :

Emergency telephone : ++49 (0) 6132 / 84463 (GBK Gefahrgut Buero GmbH, Ingelheim)

Responsible for the safety data sheet: sds@gbk-ingelheim.de

2. Hazards identification

Classification

Indications of danger : Highly flammable, Irritant, Dangerous for the environment

R-phrases:

Highly flammable.

Irritating to eyes and skin.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

3. Composition/information on ingredients

Chemical characterization (Mixture)

Preparation with ethyl acetate

Hazardous components

EC-No.	CAS-No.	Chemical name	Quantity	Classification
205-500-4	141-78-6	Ethyl acetate	< 60 %	F, Xi R11-36-66-67
295-529-9	92062-15-2	Solvent naphta (petroleum)	< 25 %	F, Xn, Xi, N R11-38-51-53-65-67
238-677-1	14634-93-6	Zinc-bis (N-ethyl-N-phenyldithiocarbamate)	< 5 %	Xi R36-53
215-222-5	1314-13-2	zinc oxide	< 1 %	N R50-53

Full text of each relevant R phrase can be found in heading 16.

Further Information

According to note P to the regulation (EC) no. 1272/2008, "Solvent naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

4. First aid measures



General information

Remove contaminated soaked clothing immediately.

If you feel unwell, seek medical advice.

Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

In the event of symptoms refer for medical treatment.

After contact with skin

Wash off with soap and plenty of water.

Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

After ingestion

Induce vomiting only upon the advice of a physician.

Attention. Beware, danger of aspiration.

Do not induce vomiting.

Summon a doctor immediately.

5. Fire-fighting measures

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Extinguishing media which must not be used for safety reasons

Full water jet.

Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases

Fire may produce:

Carbon monoxide and carbon dioxide.

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Protective suit.

Additional information

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

6. Accidental release measures

Personal precautions

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater.



Methods for cleaning up/taking up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

7. Handling and storage

Handling

Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Keep a good ventilation and air-exhaust at the place of work.

Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

Storage

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

Advice on storage compatibility

Incompatible with:

Oxidizing agents.

Nitrous acid and other nitrosating agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

8. Exposure controls/personal protection

Exposure limit values

Exposure limits (EH40)

CAS-No.	Chemical name	ml/m ³	mg/m ³	F/ml	Category	Origin
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL
1314-13-2	Zinc oxide, fume (OLD)	-	5		TWA (8 h)	OES
		-	10		STEL (15 min)	OES

Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothes before re-use.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).



TIP TOP SPECIAL CEMENT BL, free of chlorinated and aromatic hydrocarbons

00156-0083

Hand protection

Splash protection:

Protective gloves resistant to chemicals made off natural-rubber latex, Minimum coat thickness 0.6 mm, Permeation resistance (wear duration) approx. 10 minutes, i.e. protective glove <Lapren 706> made by www.kcl.de.

Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0,7 mm, permeation resistance (wear duration) > 60 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Eye protection

Eye wash bottle with pure water.

Tightly fitting goggles.

Skin protection

Solvent-resistant apron.

9. Physical and chemical properties

General information

Physical state : Liquid
Colour : Blue
Odour : Ester-like

Important health, safety and environmental information

Changes in the physical state

Boiling point : 76 °C approx.
Flash point : < - 18 °C
Lower explosion limits : 0,6 vol. %
Upper explosion limits :
Density (at 20 °C) : 0,88 g/cm³
Water solubility : Immiscible
(at 20 °C)
Viscosity / dynamic : 5500 - 6500 mPa·s
(at 20 °C)
Flow time : > 30 s 3 DIN EN ISO 2431
(at 23 °C)

Solvent content

< 85 %

Other information

Ignition temperature : 460 °C

10. Stability and reactivity

Conditions to avoid

To avoid thermal decomposition, do not overheat.
Vapour/air mixtures are explosive at intensive warming.
Heating can release vapours which can be ignited.

Materials to avoid

Nitrous acid and other nitrosating agents.
Oxidizing agents.



Hazardous decomposition products

Carbon monoxide and carbon dioxide.

An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces.

Additional information

No decomposition if stored and applied as directed.

11. Toxicological information

Empirical data on effects on humans

Irritating to eyes and skin.

Vapours may cause drowsiness and dizziness.

Effects of breathing high concentrations of vapour may include . Headache, dizziness, weakness, unconsciousness.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Further information

An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces.

12. Ecological information

Further information

Do not flush into surface water or sanitary sewer system.

Low hazard to waters.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. Disposal considerations

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances

Classified as hazardous waste.

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

14. Transport information

Land transport (ADR/RID)

UN number : 1133

ADR/RID class : 3

Classification code : F1

Safety Data Sheet according to Regulation (EU) No. 1907/2006

REMA TIP TOP GmbH

Revision date: 10.09.2010

Revision no.: 1,28

**TIP TOP SPECIAL CEMENT BL, free of chlorinated and aromatic hydrocarbons**

00156-0083

Warning plate

Hazard-no. :	33
Hazard label :	3
ADR/RID packing group :	II
Limited quantity :	LQ 6

Description of the goods

Adhesives

Other applicable information (land transport)

LQ 6: combination packaging: 5 l / 30 kg (total gross mass); trays: 1 l / 20 kg (total gross mass).

Tunnel restriction code: D/E

Transport category: 2

Additional label with symbol "fish and tree" according to subsection 5.2.1.8.3. ADR for single packagings and inner packagings with > 5 kg or 5 L, transition period ends 31.12.2010.

Marine transport

UN number :	1133
IMDG code :	3
Marine pollutant :	No
Hazard label :	3
IMDG packing group :	II
EmS :	F-E; S-D
Limited quantity :	5 L / 30 kg

Description of the goods

ADHESIVES

Other applicable information (marine transport)

Limited quantities (section 3.4): combination packaging: 5 l / 30 kg (total gross mass); trays: 5 l / 20 kg (total gross mass).

Additional label with symbol "fish and tree" according to subsection 5.2.1. IMDG Code for single packagings and inner packagings with > 5 kg or 5 L.

Segregation group: -

Air transport

UN/ID number :	1133
ICAO/IATA-DGR :	3
Hazard label :	3
ICAO packing group :	II
Limited quantity Passenger :	Y305 / 1 L
IATA-packing instructions - Passenger :	305
IATA-max. quantity - Passenger :	5 L
IATA-packing instructions - Cargo :	307
IATA-max. quantity - Cargo :	60 L

Description of the goods

ADHESIVES

15. Regulatory information**Labelling****Additional advice on labelling**

According to EC-regulations the product is to be labelled as follows:

Safety Data Sheet according to Regulation (EU) No. 1907/2006

REMA TIP TOP GmbH

Revision date: 10.09.2010

Revision no.: 1,28

TIP TOP SPECIAL CEMENT BL, free of chlorinated and aromatic hydrocarbons

00156-0083



Danger symbols :

F - Highly flammable; Xi - Irritant; N - Dangerous for the environment



F - Highly flammable

Xi - Irritant

N - Dangerous for the environment

R phrases

- 11 Highly flammable.
- 36/38 Irritating to eyes and skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 67 Vapours may cause drowsiness and dizziness.

S phrases

- 16 Keep away from sources of ignition - No smoking.
- 02 Keep out of the reach of children.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 29 Do not empty into drains.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 61 Avoid release to the environment. Refer to special instructions / Safety data sheets.

EU regulatory information

1999/13/EC (VOC) : 80 - 85 %

National regulatory information

Employment restrictions : Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing.

Water contaminating class (D) : 1 - slightly water contaminating

16. Other information

Full text of R-phrases referred to under sections 2 and 3

- 11 Highly flammable.
- 36 Irritating to eyes.
- 36/38 Irritating to eyes and skin.
- 38 Irritating to skin.
- 50 Very toxic to aquatic organisms.
- 51 Toxic to aquatic organisms.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 53 May cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

Safety Data Sheet according to Regulation (EU) No. 1907/2006

REMA TIP TOP GmbH

Revision date: 10.09.2010

Revision no.: 1,28

TIP TOP SPECIAL CEMENT BL, free of chlorinated and aromatic hydrocarbons

00156-0083



(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)