REMATIP TOP AG

Revision date: 28.05.2014

**TIP TOP SOLUTION T2-A** 

00156-0013



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

Revision No: 2.0

## 1.1. Product identifier

TIP TOP SOLUTION T2-A

Art.-No.

517 7362, 517 7363, 517 7380; 119000182

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

adhesive

### 1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG
Street: Gruber Strasse 63
Place: D-85586 Poing
Telephone +49 (0) 8121 / 707 - 0

Verantwortlich für das Sicherheitsdatenblatt: sds@gbk-ingelheim.de

<u>1.4. Emergency telephone</u> INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a) number: England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

24

#### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Indications of danger: T - Toxic

R phrases:

Irritating to eyes and skin. May cause cancer.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

Possible risks of irreversible effects.

#### **GHS** classification

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory/skin sensitization: Skin Sens. 1

Germ cell mutagenicity: Muta. 2 Carcinogenicity: Carc. 1B

Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction. May cause drowsiness or dizziness. Suspected of causing genetic defects.

May cause cancer.

Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

## Hazardous components which must be listed on the label

Trichloroethylene

Signal word: Danger

Pictograms: GHS07-GHS08

REMATIP TOP AG

00156-0013

Revision date: 28.05.2014 TIP TOP SOLUTION T2-A

Revision No: 2,0





#### **Hazard statements**

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H336 May cause drowsiness or dizziness.
 H341 Suspected of causing genetic defects.

H350 May cause cancer.

H412 Harmful to aquatic life with long lasting effects.

### **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P273 Avoid release to the environment.

## Special labelling of certain mixtures

Restricted to professional users.

### 2.3. Other hazards

Not known.

**SECTION 3: Composition/information on ingredients** 

## 3.2. Mixtures

## **Chemical characterization**

Preparation with trichloroethylene

## **Hazardous components**

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
201-167-4	Trichloroethylene	< 95 %
79-01-6	Carc. Cat. 2, Muta. Cat. 3, Xi - Irritant R45-68-67-36/38-52-53	
602-027-00-9	Carc. 1B, Muta. 2, Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Chronic 3; H350 H341 H315 H319 H317 H336 H412	
01-2119490731-36		
215-222-5	Zinc oxide	< 1 %
1314-13-2	N - Dangerous for the environment R50-53	
030-013-00-7	Aquatic Acute 1, Aquatic Chronic 1; H400 H410	
01-2119463881-32		

Full text of R and H phrases: see Section 16.

#### **Further Information**

SVHC substance [Regulation (EC) No 1907/2006, Article 57]: Trichloroethylene

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Take away from danger area and lay down affected person.

REMATIP TOP AG

Revision date: 28.05.2014

**TIP TOP SOLUTION T2-A** 

00156-0013



#### After inhalation

Move to fresh air in case of accidental inhalation of vapours.

In the event of symptoms refer for medical treatment.

#### After contact with skin

Wash off immediately with soap and plenty of water.

Consult a doctor if skin irritation persists.

#### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Revision No: 2.0

Seek medical treatment by eye specialist.

#### After ingestion

Induce vomiting only upon the advice of a physician.

Attention. Beware, danger of aspiration.

Summon a doctor immediately.

Immediately give plenty of water, if possible charcoal slurry.

#### 4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May cause cancer.

Suspected of causing genetic defects.

May cause an allergic skin reaction.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

## Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

Product does not burn, fire-extinguishing activities according to surrounding.

# Unsuitable extinguishing media

Full water jet.

## 5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide and carbon dioxide

Chlorine and traces of phosgene.

Hydrogen chloride gas.

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

### **Additional information**

Keep away from heat and sources of ignition.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

# 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

# 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Revision No: 2,0

REMATIP TOP AG

Revision date: 28.05.2014

**TIP TOP SOLUTION T2-A** 

00156-0013



### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Care for thoroughly room ventilation, if necessary suck off at workplace.

Avoid contact with skin, eyes and clothing.

#### Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

#### Advice on storage compatibility

Incompatible with:

Oxidizing agents

Aluminium powder

Alkaline metals and earth alkaline metals.

Alkaline leaches

### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

# 7.3. Specific end use(s)

adhesive

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
79-01-6	Trichloroethylene	100	550		TWA (8 h)	WEL
		150	820		STEL (15 min)	WEL

## 8.2. Exposure controls

## Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

## Protective and hygiene measures

Do not inhale vapours.

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Take off immediately all contaminated clothing.

## Eye/face protection

Eye wash bottle with pure water (EN 15154).

Tightly fitting goggles (EN 166).

## Hand protection

Protective gloves resistant to chemicals made off viton, minimum coat thickness 0,7 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove < Vitoject 890> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

REMATIP TOP AG

Revision date: 28.05.2014

Revision No: 2,0



**TIP TOP SOLUTION T2-A** 

00156-0013

# Skin protection

Long sleeved clothing (EN 368).

## Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 141).

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Black
Odour: Sweetish
Initial boiling point and boiling range: approx. 90 °C

Flash point: n.a. \*)

Lower explosion limits: 7,9 vol. %

Upper explosion limits:

Vapour pressure: 77 hPa

(at 20 °C)

Vapour density: 4,54

Density: 1,42 g/cm³ Water solubility: Immiscible

(at 20 °C)

Ignition temperature: 410 °C

Viscosity / dynamic: 2000 mPa·s

Solvent content: > 90 %

### 9.2. Other information

"\*) According to PTB instructions, trichloroethylene has no flashpoint; however, vapour and air mixtures are flammable under a stronger energy influx."

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No decomposition if stored and applied as directed.

# 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

Reactions with alkalies.

Reactions with alkali metals.

Reactions with earth alkali metals.

## 10.4. Conditions to avoid

Above 120°C, a thermic decomposition may take place.

## 10.5. Incompatible materials

Alkaline metals and alkaline earth metals., Bases., oxidizing agents, Aluminium powder

## 10.6. Hazardous decomposition products

Chlorine and traces of phosgene.

Hydrogen chloride gas

Carbon monoxide and carbon dioxide.

### **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

### Acute toxicity

REMATIP TOP AG

Revision date: 28.05.2014

**TIP TOP SOLUTION T2-A** 

00156-0013

Revision No: 2,0



Based on available data, the classification criteria are not met.

No toxicological data available.

Trichloroethylene

LD50/oral/rat: 5400 mg/kg

LD50/dermal/rabbit: > 2000 mg/kg LC50/inhalation/rat: 12500 ppm/4h

#### Irritation and corrosivity

Causes serious eye irritation.

Causes skin irritation.

### Sensitising effects

May cause an allergic skin reaction. (Trichloroethylene)

## STOT-single exposure

May cause drowsiness or dizziness. (Trichloroethylene)

## Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (Trichloroethylene)

May cause cancer. (Trichloroethylene)

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

### **Practical experience**

#### Other observations

Components of the product may be absorbed into the body through the skin. (skin absorption).

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Effects of breathing high concentrations of vapour may include:

Headache, dizziness, weakness, unconsciousness.

Hazard of lung oedema.

Skin contact or inhalation of solvents contained in this product may cause irritation of skin, eyes and mucous membranes.

### **SECTION 12: Ecological information**

## 12.1. Toxicity

Ecological data are not available.

Trichloroethylene

LC50/Pimephales promelas/ 96 h = 42,4 mg/l

EC50/Daphnia magna/48 h = 20,8 mg/l

EC50/Algae/96 h = 36,5 mg/l

Zinc oxide

EC50/Selenastrum capricornutum/72 h = 0,17 mg/l

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### 12.2. Persistence and degradability

Trichloroethylene

Biodegradable (OECD): 2,4% (14 d) [OECD 301C]

Not readily biodegradable.

## 12.3. Bioaccumulative potential

Trichloroethylene

Low bio-accumulation can be estimated because of low log Po/w. (Log Pow: 2,53)

## 12.4. Mobility in soil

Trichloroethylene

High mobility in soil.

# 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

#### 12.6. Other adverse effects

Severe hazard to waters

**REMATIP TOP AG** 

Revision date: 28.05.2014

Revision No: 2,0



TIP TOP SOLUTION T2-A

00156-0013

#### **Further information**

Do not flush into surface water or sanitary sewer system.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

### Waste disposal number of waste from residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and

sealants containing organic solvents or other dangerous substances

Classified as hazardous waste.

#### Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

## **SECTION 14: Transport information**

Land transport (ADR/RID)

**14.1. UN number:** UN1710

14.2. UN proper shipping name: TRICHLOROETHYLENE, Solution

14.3. Transport hazard class(es):6.114.4. Packing group:IIIHazard label:6.1



Classification code:

Limited quantity: 5 L / 30 kg

Transport category: 2
Hazard No: 60
Tunnel restriction code: E

Inland waterways transport (ADN)

**14.1. UN number:** UN1710

14.2. UN proper shipping name: TRICHLOROETHYLENE, Solution

 14.3. Transport hazard class(es):
 6.1

 14.4. Packing group:
 III

 Hazard label:
 6.1



Classification code:

Limited quantity: 5 L / 30 kg

Marine transport (IMDG)

**14.1. UN number:** UN1710

14.2. UN proper shipping name: TRICHLOROETHYLENE SOLUTION

14.3. Transport hazard class(es):6.114.4. Packing group:IIIHazard label:6.1

REMATIP TOP AG

Revision date: 28.05.2014

Revision No: 2,0



**TIP TOP SOLUTION T2-A** 

00156-0013



Marine pollutant: No

Limited quantity: 5 L / 30 kg EmS: F-A, S-A

Air transport (ICAO)

**14.1. UN number:** UN1710

14.2. UN proper shipping name: TRICHLOROETHYLENE SOLUTION

14.3. Transport hazard class(es):6.114.4. Packing group:IIIHazard label:6.1



Limited quantity Passenger: Y642 / 2 L

IATA-packing instructions - Passenger:655IATA-max. quantity - Passenger:60 LIATA-packing instructions - Cargo:663IATA-max. quantity - Cargo:220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practices.

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

The transport takes place only in approved and appropriate packaging.

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU** regulatory information

1999/13/EC (VOC): > 90 %

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment

restrictions for child bearing mothers and nursing.

# Additional information

Chemical prohibition regulation consider.

## 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

#### **SECTION 16: Other information**

## Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

REMATIP TOP AG

Revision date: 28.05.2014 Revision No: 2,0



00156-0013



IBC = Code International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

#### Full text of R phrases referred to under Sections 2 and 3

36/38 Irritating to eyes and skin.
45 May cause cancer.

Very toxic to aquatic organisms.Harmful to aquatic organisms.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

53 May cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

68 Possible risks of irreversible effects.

#### Full text of H statements referred to under Sections 2 and 3

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H341 Suspected of causing genetic defects.
H350 May cause capeer.

H350 May cause cancer. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

#### **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)