REMATIP TOP AG

Revision date: 01.04.2014

TIP TOP TTSEAL XXL

00156-0145



SECTION 1: Identification of the substance/mixture and of the company/undertaking

Revision No: 2,0

1.1. Product identifier

TIP TOP TTSEAL XXL

Art.-No.

593 1252, 593 1253, 593 1260

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Tyre sealing material

1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG
Street: Gruber Strasse 63
Place: D-85586 Poing
Telephone +49 (0) 8121 / 707 - 0
Verantwortlich für das Sicherheitsdatenblatt: sds@gbk-ingelheim.de

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: Xn - Harmful

R phrases:

Harmful if swallowed.

GHS classification

Hazard categories:

Acute toxicity: Acute Tox. 4

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazard Statements: Harmful if swallowed.

May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Hazardous components which must be listed on the label

Ethane-1,2-diol

Signal word: Warning

Pictograms: GHS07-GHS08





Hazard statements

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P260 Do not breathe vapour.

P270 Do no eat, drink or smoke when using this product.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P330 Rinse mouth.

P501 Dispose of contents/container to in accordance with local and national regulations.

REMATIP TOP AG

Revision date: 01.04.2014

Revision No: 2,0



TIP TOP TTSEAL XXL

00156-0145

2.3. Other hazards

Not known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Aqueous solution

Hazardous components

| po | | | | |
|------------------|--|---------|--|--|
| EC No | Chemical name | | | |
| CAS No | Classification | | | |
| Index No | GHS classification | | | |
| REACH No | | | | |
| 203-473-3 | Ethane-1,2-diol | < 35 % | | |
| 107-21-1 | Xn - Harmful R22 | | | |
| 603-027-00-1 | Acute Tox. 4, STOT RE 2; H302 H373 | | | |
| 01-2119456816-28 | | | | |
| 231-555-9 | Sodium nitrite | < 1 % | | |
| 7632-00-0 | O - Oxidizing, T - Toxic, N - Dangerous for the environment R8-25-50 | | | |
| 007-010-00-4 | Ox. Sol. 3, Acute Tox. 3, Aquatic Acute 1; H272 H301 H400 | | | |
| 01-2119471863-27 | | | | |
| 220-120-9 | 1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one | < 0.1 % | | |
| 2634-33-5 | Xn - Harmful, Xi - Irritant, N - Dangerous for the environment R22-38-41-43-50 | | | |
| 613-088-00-6 | Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1; H302 H315 H318 H317 H400 | | | |
| | | | | |

Full text of R and H phrases: see Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

After contact with skin

Wash off with soap and plenty of water.

After contact with eyes

If eye irritation persists, consult a specialist.

Rinse immediately with plenty of water, also under the eyelids.

After ingestion

Induce vomiting only upon the advice of a physician.

Immediately give plenty of water (if possible charcoal slurry).

Summon a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

Harmful if swallowed.

May cause damage to organs through prolonged or repeated exposure. [Kidney]

Inhalation of vapours may cause mild irritation to the mucous membrane.

Repeated or prolonged exposure may cause irritation of eyes and skin.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

REMATIP TOP AG

Revision date: 01.04.2014

TIP TOP TTSEAL XXL

00156-0145



Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

Sand

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

Additional information

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Revision No: 2.0

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Avoid contact with the skin and the eyes.

Advice on protection against fire and explosion

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Advice on storage compatibility

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Tyre sealing material

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m³ | fibres/ml | Category | Origin |
|----------|-------------------------|-----|-------|-----------|---------------|--------|
| 107-21-1 | Ethane-1,2-diol, vapour | 20 | 52 | | TWA (8 h) | WEL |
| | | 40 | 104 | | STEL (15 min) | WEL |

REMATIP TOP AG

Revision date: 01.04.2014

Revision No: 2.0







Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Avoid contact with eyes and skin.

Wash hands before breaks and at the end of workday.

When using, do not eat, drink or smoke.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Safety goggles with side protection (EN 166).

Hand protection

Protective gloves resistant to chemicals made off natural-rubber latex, minimum coat thickness 0.6 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Lapren 706> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (EN 368).

Respiratory protection

No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Viscous
Colour: Black
Odour: Mild

pH-Value: 8 - 10

Melting point: < 0 °C

Initial boiling point and boiling range: approx. 100 °C

Flash point: n.a. Lower explosion limits: n.d.

Vapour pressure: approx. 23 hPa
Density (at 20 °C): 1,1 g/cm³
Water solubility: Partially miscible

(at 20 °C)

Ignition temperature: n.d.
Solvent content: < 35 %

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat. Heating can release vapours which can be ignited.

Print date: 05.06.2014 GB - EN Page 4 of 7



REMATIP TOP AG

Revision date: 01.04.2014

TIP TOP TTSEAL XXL

00156-0145



10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

Revision No: 2.0

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Harmful if swallowed.

No toxicological data available.

Sodium nitrite

LD50/oral/rat: 180 mg/kg

Ethane-1,2-diol

LD50/oral/rat: 5840 mg/kg LD50/dermal/rabbit: 9530 mg/kg

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

May cause damage to organs through prolonged or repeated exposure. (Ethane-1,2-diol)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

Inhalation of vapours may cause mild irritation to the mucous membrane.

Repeated or prolonged exposure may cause irritation of eyes and skin.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Low hazard to waters.

Further information

Ecological injuries are not known or expected under normal use.

Do not flush into surface water or sanitary sewer system.

REMATIP TOP AG

Revision date: 01.04.2014

Revision No: 2.0

TIP TOP TTSEAL XXL

00156-0145



SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances

Classified as hazardous waste.

Contaminated packagingEmpty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID); Marine transport (IMDG); Air transport (ICAO); Inland waterways transport (ADN)

14.1. UN number:

No hazardous material as defined by the transport regulations.

14.2. UN proper shipping name:

No hazardous material as defined by the transport regulations.

14.3. Transport hazard class(es):

No hazardous material as defined by the transport regulations.

14.4. Packing group:

No hazardous material as defined by the transport regulations.

14.5. Environmental hazards

No hazardous material as defined by the transport regulations.

14.6. Special precautions for user

No hazardous material as defined by the transport regulations.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No hazardous material as defined by the transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

1999/13/EC (VOC):

0 %

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment

restrictions for child bearing mothers and nursing.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

Changes in chapter: 1

REMATIP TOP AG

Revision date: 01.04.2014 Revision No: 2.0

TIP TOP TTSEAL XXL

00156-0145



Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC = Code International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Full text of R phrases referred to under Sections 2 and 3

| 08 | Contact with combustible material may cause fire. |
|----|---|
|----|---|

22 Harmful if swallowed. 25 Toxic if swallowed. 38 Irritating to skin.

Risk of serious damage to eyes. 41

May cause sensitisation by skin contact. 43

50 Very toxic to aquatic organisms.

Full text of H statements referred to under Sections 2 and 3

May intensify fire; oxidiser. H301 Toxic if swallowed. H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eve damage.

H373

May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)